

Locking Devices, Twist-Lock®, Industrial, Flush Receptacle, 20A 3-Phase Delta 250V AC, 3-Pole 4-Wire Grounding, Non-NEMA, Screw Terminal, Black

By Hubbell Wiring Device-Kellems  
Catalog # [HBL7310BG](#)

Locking Devices, Twist-Lock®, Industrial, Flush Receptacle, 20A 3-Phase Delta 250V AC, 3-Pole 4-Wire Grounding, Non-NEMA, Screw Terminal, Black

Features

- High-impact, abuse-resistant nylon face
- Wire restraint recess for both back and side wiring, greatly reduces the possibility of loosening the terminal connection
- Face color coding by voltage facilitates locating and mating of proper devices
- All-brass mounting and grounding system provides a lower resistance ground path and greater resistance to corrosion than steel mounting systems

Application

Heavy Duty Industrial

Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - Withstands 2,000V minimum, Environmental - Flammability - V2 or better per UL94/CSA 22.2 No.0.17, Environmental - Moisture Resistance - IP20 Suitability, Environmental - Operating Temperatures - Maximum Continuous 75°C Minimum -40°C (w/o impact), Mechanical - Terminal Accommodation - #16 AWG - #8 AWG solid or stranded copper wire only., Mechanical - Terminal Identification - Terminals identified in accordance with UL 498

Specifications

|                          |                                                                                                                                       |
|--------------------------|---------------------------------------------------------------------------------------------------------------------------------------|
| Environmental Conditions | Indoor Dry Unless Protected By Additional Means                                                                                       |
| EU RoHS Indicator        | Yes                                                                                                                                   |
| Nema Rating              | Non-NEMA                                                                                                                              |
| Industry Standard(s)     | <ul style="list-style-type: none"><li>• Certified to CSA C22.2 No.42</li><li>• Fed.Spec. W-C-596</li><li>• Listed to UL 498</li></ul> |

Conductor

|                 |                   |
|-----------------|-------------------|
| Number Of Wires | 3-Wire            |
| Wire Size       | #16 AWG to #8 AWG |
| Number Of Poles | 2-Pole            |

Current

|                 |      |
|-----------------|------|
| Amperage Rating | 20 A |
|-----------------|------|



|                            |                            |
|----------------------------|----------------------------|
| Voltage Rating Description | 250 VAC                    |
| Dielectric Strength        | Withstands 2,000V minimum  |
| Current Rating             | 20 A                       |
| Voltage Rating             | 250 VAC                    |
| Connectivity               | Back Wired Screw Terminals |
| Phase                      | Single Phase               |
| Current / Amperage Rating  | 20 A                       |

Dimensions

|              |                             |
|--------------|-----------------------------|
| Length       | 3.61 in                     |
| Display Size | Standard Sized Product      |
| Weight       | 0.25 lb.                    |
| Height       | 1.28 in                     |
| Width        | 1.39 in                     |
| Dimensions   | 3.61 in x 1.39 in x 1.28 in |

General

|                              |                                                                                                                                                                                                                                       |
|------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Color                        | Black                                                                                                                                                                                                                                 |
| Specifications               | <ul style="list-style-type: none"><li>• Base - Glass-Reinforced thermoplastic polyester (RTP)</li><li>• Contacts - Brass</li><li>• Face - Nylon</li><li>• Mounting Strap - Brass</li><li>• Terminal Screws - #10 - 32 Brass</li></ul> |
| UPC                          | 783585333649                                                                                                                                                                                                                          |
| Type                         | Receptacle                                                                                                                                                                                                                            |
| Material - Mounting Hardware | Screw Mounting                                                                                                                                                                                                                        |
| Item Type                    | 20A Single Flush Receptacle                                                                                                                                                                                                           |
| Material                     | Nylon                                                                                                                                                                                                                                 |

Logistics

|                 |    |
|-----------------|----|
| Carton Quantity | 10 |
|-----------------|----|

Operational

|                       |                                                          |
|-----------------------|----------------------------------------------------------|
| Operating Temperature | Maximum continuous 75°C and minimum -40°C without Impact |
|-----------------------|----------------------------------------------------------|

Product Assets

- Catalog [English]
  - Catalog Page [English]
  - Catalog Page [English]
  - Installation Manual [English]
- 

