

Locking Devices, Twist-Lock®, Industrial, Receptacle, 50A 250V DC/ 600V AC, 3-Pole 4-Wire Grounding, Non-NEMA, Screw Terminal, Phenolic Black

By Hubbell Wiring Device-Kellems
Catalog # [HBL7379](#)

Locking Devices, Twist-Lock®, Industrial, Receptacle, 50A 250V DC/ 600V AC, 3-Pole 4-Wire Grounding, Non-NEMA, Screw Terminal, Phenolic Black

Features

- Thermoset construction offers high heat resistance
- Armored housing provides superior impact resistance
- One piece contacts provide low operating temperatures

Application

Heavy Duty Industrial

Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - Withstands 2,000V minimum, Environmental - Flammability - UL 94 V0, Environmental - Operating Temperatures - Maximum continuous 75°C minimum -40°C (w/o impact), Mechanical - Terminal Accommodation - #10 AWG - #6 AWG solid or stranded copper wire only

Specifications

Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	No
Nema Rating	Non-NEMA
Industry Standard(s)	• Certified to CSA C22.2 No.42 • Listed to UL 498

Conductor

Number Of Wires	4-Wire
Wire Size	#8 AWG to #4 AWG
Number Of Poles	3-Pole

Current

Amperage Rating	50 A
Voltage Rating Description	250 VDC/600 VAC
Dielectric Strength	Withstands 2,000V minimum
Current Rating	50 A



Voltage Rating	250 VDC/600 VAC
Connectivity	Screw Terminals
Phase	Multi Phase
Current / Amperage Rating	50 A

Dimensions

Length	3.28 in
Weight	0.75 lb.
Height	2.36 in
Width	2.12 in
Dimensions	3.28 in x 2.12 in x 2.36 in

General

Color	Black
Specifications	• Body - Phenolic • Contacts - Brass • Face - Phenolic • Insulator - Phenolic • Terminal Screws - Steel
UPC	783585237176
Type	Receptacle
Material - Mounting Hardware	Screw Mounting
Item Type	50A Receptacle
Material	Phenolic

Logistics

Pallet Quantity	950
Carton Quantity	10

Operational

Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
-----------------------	--

Product Assets

[Catalog \[English\]](#)
[Catalog Page \[English\]](#)
[Installation Manual \[Spanish, French, English\]](#)