

Locking Devices, Twist-Lock®, Industrial, Flanged Inlet, 20A 3-Phase Wye 120/208V AC, 4-Pole 4-Wire Non-Grounding, Non-NEMA, Screw Terminal, White

By Hubbell Wiring Device-Kellems
Catalog # [HBL7408C](#)

Locking Devices, Twist-Lock®, Industrial, Flanged Inlet, 20A 3-Phase Wye 120/208V AC, 4-Pole 4-Wire Non-Grounding, Non-NEMA, Screw Terminal, White

Features

- Impact resistant thermoplastic construction
- Backwired terminations for ease of installation
- #10-32 Multiple drive terminal screws (Slotted, Phillips, Robertson)
- Mounting screws included

Application

Extra Heavy Duty Industrial

Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - Withstands 2,000V minimum, Environmental - Flammability - HB or better per UL94/CSA 22.2 No.0.17, Environmental - Moisture Resistance - IP20 Suitability, Environmental - Operating Temperatures - Maximum Continuous 75°C Minimum -40°C (w/o impact), Mechanical - Terminal Accommodation - #16 AWG - #10 AWG solid or stranded copper wire only, Mechanical - Terminal Identification - Terminals identified in accordance with UL 498

Specifications

Standards - RoHS Compliance Status	CM
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	Yes
Nema Rating	Non-NEMA
Industry Standard(s)	• Certified to CSA C22.2 No.42 • Fed.Spec. W-C-596 • Listed to UL 498

Conductor

Number Of Wires	4-Wire
Wire Size	#16 AWG to #10 AWG
Number Of Poles	4-Pole

Current

Amperage Rating	20 A
Voltage Rating Description	3 Phase WYE 120/208 VAC



Dielectric Strength	Withstands 2,000V minimum
Current Rating	20 A
Voltage Rating	3 Phase WYE 120/208 VAC
Connectivity	Back Wired Screw Terminals
Phase	Three Phase
Current / Amperage Rating	20 A

Dimensions

Length	3.06 in
Display Size	Standard Sized Product
Weight	0.25 lb.
Height	2.30 in
Width	3.06 in
Dimensions	3.06 in x 3.06 in x 2.30 in

General

Color	White
Specifications	• Assembly Screws - Steel - nickel plated • Blades - Brass • Housing - Nylon • Mounting Screw - Nickel plated brass • Terminal Clamp - Cold rolled steel - nickel plated • Terminal Retainer - Clear polycarbonate • Terminal Screws - #10-32 Brass (Phillips / Slotted / Robertson)

UPC	783585037547
Type	Flanged Inlet
Material - Mounting Hardware	Screw Mounting
Insulation	Insulated Body
Item Type	20A Insulgrip® Flanged Inlet
Material	Nylon

Logistics

Carton Quantity	10
-----------------	----

Operational

Temperature Rating	• Maximum Continuous: 75° C
--------------------	---

Operating Temperature

- Minimum Continuous: -40° C w/o impact, -25° with impact.
- Maximum continuous 75°C and minimum -40°C without Impact

Product Assets

- [Catalog \[English\]](#)
- [Catalog Page \[English\]](#)
- [Catalog Page \[English\]](#)
- [Installation Manual \[English\]](#)



A Hubbell brand