

HUBBELL

Wiring Device

[Locking Devices, Twist-Lock®, Industrial, Male Plug, 20A 3-Phase 120/208VAC, 4-Pole 4-Wire Non-Grounding, Non- NEMA, Screw Terminal, Black and White](#)

By Hubbell Wiring Device-Kellems

Catalog # [HBL7411C](#)

Locking Devices, Twist-Lock®, Industrial, Male Plug, 20A 3-Phase 120/208VAC, 4-Pole 4-Wire Non-Grounding, Non- NEMA, Screw Terminal, Black and White



Features

- Ribbed nylon housing provides a secure grip and impact and chemical resistance.
- Superior cord grip design protects terminations from excess strain.
- Clear, funnel shaped wire entry for ease of termination.
- Integral dust shield protects wiring chamber from dust or contaminants.

Application

Extra Heavy Duty Industrial

Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - Withstands 2,000V minimum, Environmental - Flammability - HB or better per UL94/CSA 22.2 No.0.17, Environmental - Moisture Resistance - IP20 Suitability, Environmental - Operating Temperatures - Maximum Continuous 75°C Minimum -40°C (w/o impact), Mechanical - Terminal Accommodation - #16 AWG - #8 AWG stranded copper wire only., Mechanical - Terminal Identification - Terminals identified in accordance with UL 498

Specifications

Standards - RoHS Compliance Status
CM
Environmental Conditions
Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator
Yes
Industry Standard(s)

- Certified to CSA C22.2 No.42
- Fed.Spec. W-C-596
- Listed to UL 498

Conductor

Number Of Wires
4-Wire
Wire Size
#16 AWG to #8 AWG
Number Of Poles
4-Pole
Cable Range
0.350 - 1.150 in

Configuration

Cord Type
All Listed Portables

Current

Amperage Rating
20 A
Voltage Rating Description
3 Phase WYE 120/208 VAC
Dielectric Strength
Withstands 2,000V minimum
Current Rating
20 A
Voltage Rating
3 Phase WYE 120/208 VAC
Connectivity
Screw Terminals
Phase
Three Phase
Current / Amperage Rating
20 A

Dimensions

Length
2.33 in
Display Size
Standard Sized
Weight
0.3 lb.
Height
2.75 in
Width
2.33 in
Dimensions
2.33 in x 2.33 in x 2.75 in

General

Color
Black, White
Cord Range
0.350"-1.150" (9-29)
Specifications

- Assembly Screws - Steel - nickel plated

- Blades - Brass
- Housing / Cord Clamp - Nylon
- Terminal Clamp - Cold rolled steel – nickel plated
- Terminal Retainer - Clear polycarbonate
- Terminal Screws - #10-32 Brass (Phillips / Slotted / Robertson)

UPC

783585037561

Type

Plugs

Material - Mounting Hardware

Cord Mounted

Item Type

20A Male Non-Grounding Insulgrip® Plug

Material

Nylon

Logistics

Pallet Quantity

3060

Carton Quantity

30

Operational

Operating Temperature

Maximum continuous 75°C and minimum -40°C without Impact

Product Assets

[Catalog \[English\]](#)

[Catalog Page \[English\]](#)

[Installation Manual \[English\]](#)

The Hubbell logo features the word "HUBBE" in a bold, black, sans-serif font. The letters are partially enclosed by a thick, yellow, curved line that forms a semi-circle around the top and sides of the text. The line is thicker on the left and tapers slightly towards the right.

HUBBE

