


Non-NEMA Twist-Lock Devices

Non-NEMA 20 Amp, 250, 125/250 Volts and 3ØY 120/208 Volts AC
2 Pole, 3 Wire, Grounding and 3 Pole, 3 Wire, Non-Grounding

For Replacement Use Only

IP20
SUITABILITY

Connector Bodies

Description	Cord Dia.	Catalog Number	
Black and white nylon.	.360"- .930" (9-24)	HBL7314GCB	HBL7314C
Corrosion resistant, yellow nylon.	.360"- .930" (9-24)	—	HBL73CM14C

Note: See pages C-52 and C-53 for accessories.

Single Flush Receptacles

Description	Catalog Number	
Black nylon face, back wired.	HBL7310BG	HBL7310B

Note: See page C-52 for accessories.

Flanged Receptacles

Description	Catalog Number	
Nylon casing, back wired.	—	HBL3326C

Note: See page C-52 for accessories.

IP20
SUITABILITY

For Replacement Use Only

Connector Bodies

Description	Cord Dia.	Catalog Number	
Black and white nylon.	.350"-1.150" (9-29)	HBL7413GCB	HBL7413C

Note: See pages C-52 and C-53 for accessories.

Single Flush Receptacles

Description	Catalog Number	
Black thermoset, back wired.	HBL7410BG	HBL7410B
Mounted on a 4" (101.6) round metal cover.	—	HBL7417B

Note: See page C-52 for accessories.

Flanged Receptacles

Description	Catalog Number	
Nylon casing, back wired.	—	HBL7409C

Note: See page C-52 for accessories.


The devices shown on this page are not listed by Underwriters Laboratories Inc. and are for replacement use only in existing installations.

CAUTION: To avoid electrical shock, review premises carefully and do not use if slot or blade configuration (design) is already in a circuit having a rating differing from the rating of this device.


Dimensions in Inches (mm)



HBL7314C




HBL7310B




HBL3326C



HBL7413GCB



HBL7410BG



HBL7409C