

Locking Devices, Midget Twist-Lock®, Valise®, Male Plug, 15A 125V, 2-Pole 2-Wire Non Grounding, NEMA ML-1P, Screw Terminal, Black.

By Hubbell Wiring Device-Kellems
Catalog # [HBL7465V](#)

Locking Devices, Midget Twist-Lock®, Valise®, Male Plug, 15A 125V, 2-Pole 2-Wire Non Grounding, NEMA ML-1P, Screw Terminal, Black.

Features

- Fully insulated, abuse resistant nylon housing
- Powerful, cord-gripping jaws
- Totally insulated body adds extra measure of safety

Application

Industrial/Commercial

Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - Withstands 2,000V minimum, Environmental - Flammability - HB or better per UL94/CSA 22.2 No.0.17, Environmental - Moisture Resistance - IP20 Suitability, Environmental - Operating Temperatures - Maximum Continuous 75°C Minimum -40°C (w/o impact), Mechanical - Terminal Accomodation - #18 AWG - #14 AWG stranded copper wire only., Mechanical - Terminal Identification - Terminals identified in accordance with UL 498

Specifications

Standards - RoHS Compliance Status	CM
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	Yes
Nema Rating	ML-1P
Industry Standard(s)	Fed.Spec.W-C-596

Conductor

Number Of Wires	2-Wire
Wire Size	#18 AWG to #14 AWG
Number Of Poles	2-Pole
Cable Range	0.220 - 0.385 in

Configuration

Cord Type	All Listed Portables
-----------	----------------------

Current

Amperage Rating	15 A
Voltage Rating Description	125 V
Dielectric Strength	Withstands 2,000V minimum



Current Rating	15 A
Voltage Rating	125 V
Connectivity	Pressure Terminal Screws
Phase	Single Phase
Current / Amperage Rating	15 A

Dimensions

Length	1.25 in
Display Size	Midget Locking
Weight	0.05 lb.
Height	1.06 in
Width	1.06 in
Dimensions	1.25 in x 1.06 in x 1.06 in

General

Color	Black
Cord Range	0.220"-0.385"(5.6-9.8)
Specifications	• Blades - Brass • Body Holding Screws - Steel - Zinc plated • Housing - Nylon • Terminal Clamps - Steel - Nickel plated • Terminal Screws - #6 - 32 Steel (Philips / Slotted / Robertson)
UPC	783585237282
Type	Plugs
Material - Mounting Hardware	Cord Mounted
Item Type	15A Midget Twist-Lock® Valise® Plug
Material	Nylon

Logistics

Pallet Quantity	8400
Carton Quantity	10

Operational

Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
-----------------------	--

Product Assets

[Catalog \[English\]](#)

[Catalog Page \[English\]](#)

[Installation Manual \[English\]](#)



A Hubbell brand