

Locking Devices, Midget Twist-Lock®, Industrial, Female Valise® Connector, 15A 125/250V AC, 3-Pole 3-Wire Non Grounding, NEMA ML-3R

By Hubbell Wiring Device-Kellems
Catalog # [HBL7484V](#)

Locking Devices, Midget Twist-Lock®, Industrial, Female Valise® Connector, 15A 125/250V AC, 3-Pole 3-Wire Non Grounding, NEMA ML-3R, With Insulation Displacement Terminal, Black.

Features

- Fully insulated, abuse resistant nylon housing
- Insulation displacement terminals reduce wiring time
- Insulation displacement terminal

Application

Heavy Duty Industrial

Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - Withstands 2,000V minimum, Environmental - Flammability - HB or better per UL94/CSA 22.2 No.0.17, Environmental - Moisture Resistance - IP20 Suitability, Environmental - Operating Temperatures - Maximum Continuous 75°C Minimum -40°C (w/o impact), Mechanical - Terminal Accomodation - #18 AWG - #14 AWG stranded copper wire only., Mechanical - Terminal Identification - Terminals identified in accordance with UL 498

Specifications

Standards - RoHS Compliance	CM
Status	
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	Yes
Nema Rating	ML-3R
Industry Standard(s)	• Certified to CSA C22.2 No.42 • Listed to UL 498

Conductor

Number Of Wires	3-Wire
Wire Size	#18 AWG to #14 AWG
Number Of Poles	3-Pole
Cable Range	0.300 - 0.430 in
Conductor Range	#14 AWG to #12 AWG

Current

Amperage Rating	15 A
Voltage Rating Description	125/250 V
Dielectric Strength	Withstands 2,000V minimum



Current Rating	15 A
Voltage Rating	125/250 V
Connectivity	Insulation Displacement
Current / Amperage Rating	15 A

Dimensions

Length	1.19 in
Display Size	Midget Locking
Weight	0.10 lb.
Height	1.98 in
Width	1.19 in
Dimensions	1.19 in x 1.19 in x 1.98 in

General

Color	Black
Cord Range	0.300"-0.430"(7.6-10.9)
Specifications	• Body Holding Screws - Steel - Zinc plated • Contacts - Brass • Housing - Nylon • Insulation Displacement Terminals - Brass

UPC	783585237398
Type	Connector Body
Material - Mounting Hardware	Cord Mounted
Insulation	Insulated Body
Item Type	15A Midget Twist-Lock® Valise® Connector
Material	Nylon

Logistics

Pallet Quantity	7800
Carton Quantity	10

Operational

Temperature Rating	• Maximum Continuous: 75° C • Minimum Continuous: -40° C w/o impact, -25° with impact.
Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact

Product Assets

[Catalog \[English\]](#)

[Catalog Page \[English\]](#)

[Installation Manual \[English\]](#)



A Hubbell brand