

Locking Devices, Midget Twist-Lock®, Industrial, Male Valise® Plug, 15A 125/250V AC, 3-Pole 3-Wire Non-Grounding, NEMA ML-3P

By Hubbell Wiring Device-Kellems
Catalog # [HBL7485V](#)

Locking Devices, Midget Twist-Lock®, Industrial, Male Valise® Plug, 15A 125/250V AC, 3-Pole 3-Wire Non-Grounding, NEMA ML-3P, With Insulation Displacement Terminal, Black.

Features

- Fully insulated, abuse resistant nylon housing
- Insulation displacement terminals reduce wiring time
- Insulation displacement terminal
- Totally insulated body adds extra measure of safety

Application

Industrial/Commercial

Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - Withstands 2,000V minimum, Environmental - Flammability - HB or better per UL94/CSA 22.2 No.0.17, Environmental - Moisture Resistance - IP20 Suitability, Environmental - Operating Temperatures - Maximum Continuous 75°C Minimum -40°C (w/o impact), Mechanical - Terminal Accomodation - #18 AWG - #14 AWG stranded copper wire only., Mechanical - Terminal Identification - Terminals identified in accordance with UL 498

Specifications

Standards - RoHS Compliance Status	CM
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	Contact Manufacturer
Nema Rating	ML-3P
Industry Standard(s)	Fed.Spec.W-C-596

Conductor

Number Of Wires	3-Wire
Wire Size	#18 AWG to #14 AWG
Number Of Poles	3-Pole
Cable Range	0.300 - 0.430 in

Configuration

Cord Type	All Listed Portables
-----------	----------------------

Current

Amperage Rating	15 A
Voltage Rating Description	125/250 V



Dielectric Strength	Withstands 2,000V minimum
Current Rating	15 A
Voltage Rating	125/250 V
Connectivity	Insulation Displacement
Phase	Single Phase
Current / Amperage Rating	15 A

Dimensions

Length	1.61 in
Display Size	Midget Locking
Weight	0.10 lb.
Height	1.18 in
Width	1.18 in
Dimensions	1.61 in x 1.18 in x 1.18 in

General

Color	Black
Cord Range	0.300"-0.430"(7.6-10.9)
Specifications	• Blades - Brass • Body Holding Screws - Steel - Zinc plated • Housing - Nylon • Insulation Displacement Terminals - Brass

UPC	783585237435
Type	Plugs
Material - Mounting Hardware	Cord Mounted
Item Type	15A Midget Twist-Lock® Valise® Plug
Material	Nylon

Logistics

Pallet Quantity	7150
Carton Quantity	10

Operational

Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
-----------------------	--

Product Assets

[Catalog \[English\]](#)

[Catalog Page \[English\]](#)

[Installation Manual \[English\]](#)



A Hubbell brand