

Locking Devices, Midget Twist-Lock®, Industrial, Flanged Inlet, 15A 125/250V AC, 3-Pole 3-Wire Non Grounding, NEMA ML-3P, Stainless Steel Flange.

By Hubbell Wiring Device-Kellems
Catalog # [HBL7486](#)

Locking Devices, Midget Twist-Lock®, Industrial, Flanged Inlet, 15A 125/250V AC, 3-Pole 3-Wire Non Grounding, NEMA ML-3P, Screw Terminal, Stainless Steel Flange.

Features

- Stainless Steel mounting flange
- High heat resistant phenolic base

Application

Heavy Duty Industrial

Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - Withstands 2,000V minimum, Environmental - Flammability - HB or better per UL94/CSA 22.2 No.0.17, Environmental - Moisture Resistance - IP20 Suitability, Environmental - Operating Temperatures - Maximum Continuous 75°C, Minimum -40°C (w/o impact), Mechanical - Terminal Accommodation - #18 AWG - #14 AWG solid or stranded copper wire only., Mechanical - Terminal Identification - Terminals identified in accordance with UL 498

Specifications

Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	No
Nema Rating	ML-3P
Industry Standard(s)	Listed to UL 498

Conductor

Number Of Wires	3-Wire
Wire Size	#18 AWG to #14 AWG
Number Of Poles	3-Pole

Current

Amperage Rating	15 A
Voltage Rating Description	125/250 V
Dielectric Strength	Withstands 2,000V minimum
Current Rating	15 A
Voltage Rating	125/250 V
Connectivity	Screw Terminals
Phase	Single Phase
Current / Amperage Rating	15-A



Dimensions

Length	2.06 in
Display Size	Midget Locking
Weight	0.05 lb.
Height	0.98 in
Width	1.63 in
Dimensions	2.06 in x 1.63 in x 0.98 in

General

Color	Black, Stainless
Cord Range	0.220"-0.385"(5.6-9.8)
Specifications	• Base - Phenolic • Blades - Brass • Flange - Stainless Steel • Terminal Screws - #5-40 Brass
UPC	783585237442
Type	Flanged Inlet
Material - Mounting Hardware	Screw Mounting
Insulation	Insulated Body
Item Type	15A Midget Twist-Lock® Flanged Inlet
Material	Stainless Steel

Logistics

Pallet Quantity	5000
Carton Quantity	10

Operational

Temperature Rating	• Maximum Continuous: 75° C • Minimum Continuous: -40° C w/o impact, -25° with impact.
Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact

Product Assets

[Catalog \[English\]](#)
[Catalog Page \[English\]](#)