

Locking Devices, Twist-Lock®, Industrial,
Panel Mount Receptacle, 15A 125V, 2-Pole
2-Wire Non Grounding, L1-15R, 1 and 15/16”
Mounting Dimension

By Hubbell Wiring Device-Kellems
Catalog # [HBL7498](#)

Twist-Lock® Industrial Panel Mount Receptacle 15A

Features

- Thermoset construction offers high heat resistance
- High performance copper alloy contacts
- Corrosion resistant zinc plated steel one-piece mounting strap

Application

Heavy Duty Industrial

Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - Withstands 2,000V minimum, Environmental - Flammability - HB or better per UL94/CSA 22.2 No.0.17, Environmental - Operating Temperatures - Maximum Continuous 75°C Minimum -40°C (w/o impact), Mechanical - Terminal Accommodation - #18 AWG-#12 AWG solid or stranded copper wire only, Mechanical - Terminal Identification - Terminals identified in accordance with UL 498

Specifications

Standards - RoHS Compliance Status	CM
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	No
Nema Rating	L1-15R
Industry Standard(s)	• Certified to CSA C22.2 No.42 • Listed to UL 498

Conductor

Number Of Wires	2-Wire
Wire Size	#18 AWG to #12 AWG
Number Of Poles	2-Pole

Current

Amperage Rating	15 A
Voltage Rating Description	125 V
Dielectric Strength	Withstands 2,000V minimum



Current Rating	15 A
Voltage Rating	125 V
Connectivity	Screw Terminals
Phase	Single Phase
Current / Amperage Rating	15 A

Dimensions

Length	2.34 in
Display Size	Standard Sized Product
Weight	0.15 lb.
Height	1.14 in
Width	1.39 in
Dimensions	2.34 in x 1.39 in x 1.14 in

General

Specifications	• Contacts - Brass • Housing - Molded Thermoset • Mounting Screw - Steel-zinc-plated • Terminal Screws - Brass
UPC	783585237534
Type	Receptacle
Material - Mounting Hardware	Screw Mounting
Item Type	15A Non-Grounding Panel Mount Single Receptacle
Material	Thermoplastic

Logistics

Carton Quantity	10
-----------------	----

Operational

Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
Horsepower - Maximum	0.5

Product Assets

[Catalog \[English\]](#)
[Catalog Page \[English\]](#)