

HUBBELL
Wiring Device-Kellems

**Locking Devices, Twist-Lock®, Industrial,
Flanged Receptacle, 15A 2-Pole 2-Wire Non
Grounding, L1-15R, Screw Terminal, White**

By Hubbell Wiring Device-Kellems

Catalog # [HBL7526C](#)

Locking Devices, Twist-Lock®, Industrial, Flanged Receptacle, 15A
2-Pole 2-Wire Non Grounding, L1-15R, Screw Terminal, White



Features

- Impact resistant thermoplastic construction
- Backwired terminations for ease of installation
- #8-32 Multiple drive terminal screws (Slotted, Phillips, Robertson)
- Mounting screws included

Application

Insulgrip

Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - Withstands 2,000V minimum, Environmental - Flammability - HB or better per UL94/CSA 22.2 No.0.17, Environmental - Moisture Resistance - IP20 Suitability, Environmental - Operating Temperatures - Maximum Continuous 75°C, Minimum -40°C (w/o impact), Mechanical - Terminal Accommodation - #18 AWG - #10 AWG solid or stranded copper wire only., Mechanical - Terminal Identification - Terminals identified in accordance with UL 498

Specifications

Standards - RoHS Compliance Status	CM
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	Yes
Nema Rating	L1-15R
Industry Standard(s)	Listed to UL 498

Conductor

Number Of Wires	2-Wire
Wire Size	#18 AWG to #10 AWG
Number Of Poles	2-Pole

Current

Amperage Rating	15 A
Voltage Rating Description	125 V
Dielectric Strength	Withstands 2,000V minimum
Current Rating	15 A
Voltage Rating	125 V
Connectivity	Screw Terminals
Phase	Single Phase
Current / Amperage Rating	15 A



A Hubbell brand

Dimensions

Length	2.56 in
Display Size	Standard Sized Product
Weight	0.15 lb.
Height	1.72 in
Width	2.56 in
Dimensions	2.56 in x 2.56 in x 1.72 in

General

Color	White
Specifications	• Assembly Screws - Steel – nickel plated • Contacts - Brass • Housing - Nylon • Mounting Screw - Nickel plated brass • Terminal Clamp - Cold rolled steel – nickel plated • Terminal Retainer - Clear polycarbonate • Terminal Screws - #8-32 Brass (Phillips / Slotted / Robertson)
UPC	783585178059
Type	Receptacle
Material - Mounting Hardware	Screw Mounting
Item Type	15A Non-Grounding Insulgrip® Flanged Receptacles
Material	Nylon

Logistics

Carton Quantity	10
-----------------	----

Operational

Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
Horsepower - Maximum	0.5

Product Assets

- [Catalog \[English\]](#)
- [Catalog Page \[English\]](#)
- [Catalog Page \[English\]](#)
- [Installation Manual \[Spanish, French, English\]](#)