

Locking Devices, Midget Twist-Lock®, Industrial, Male Plug, 15A 125V, 2-Pole 2-Wire Non Grounding, L1-15P, Screw Terminal, Black and White

By Hubbell Wiring Device-Kellems
Catalog # [HBL7545C](#)

Locking Devices, Midget Twist-Lock®, Industrial, Male Plug, 15A 125V, 2-Pole 2-Wire Non Grounding, L1-15P, Screw Terminal, Black and White

Features

- Ribbed nylon housing provides secure, impact and chemical resistant grip
- Superior cord grip design protects terminations from excess strain
- Integral VARI-SIZE insert accomodates a wide range of cord diameters (.22 to .72 in.)

Application

Industrial/Commercial

Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - Withstands 2,000V minimum, Environmental - Flammability - HB or better per UL94/CSA 22.2 No.0.17, Environmental - Moisture Resistance - IP20 Suitability, Environmental - Operating Temperatures - Maximum Continuous 75°C, Minimum -40°C (w/o impact), Mechanical - Terminal Accommodation - #18 AWG - #10 AWG stranded copper wire only., Mechanical - Terminal Identification - Terminals identified in accordance with UL 498

Specifications

Standards - RoHS Compliance Status	CM
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	Yes
Nema Rating	L1-15P
Industry Standard(s)	• Certified to CSA C22.2 No. 42 • Fed. Spec W-C-596 • Listed to UL 498

Conductor

Number Of Wires	3-Wire
Wire Size	#14 AWG to #12 AWG
Number Of Poles	2-Pole
Cable Range	0.230 - 0.720 in

Configuration



Cord TypeAll Listed Portables

Current

Amperage Rating	15 A
Voltage Rating Description	125 V
Dielectric Strength	Withstands 2,000V minimum
Current Rating	15 A
Voltage Rating	125 V
Connectivity	Pressure Terminal Screws
Phase	Single Phase
Current / Amperage Rating	15 A

Dimensions

Length	1.96 in
Display Size	Standard Sized
Weight	0.15 lb.
Height	1.52 in
Width	1.52 in
Dimensions	1.96 in x 1.52 in x 1.52 in

General

Color	Black, White
Cord Range Specifications	0.230"-0.720"(5.8-18.3) • Assembly Screws - Steel – nickel plated • Blades - Brass • Housing / Cord Clamp - Nylon • Terminal Clamp - Cold rolled steel – nickel plated • Terminal Retainer - Clear polycarbonate • Terminal Screws - #8-32 Brass (Phillips / Slotted / Robertson)
UPC	783585178509
Type	Plugs
Material - Mounting Hardware	Cord Mounted
Item Type	Plug
Material	Composite

Logistics

Pallet Quantity	3600	Horsepower - Maximum	0.5
Carton Quantity	10		
Operational		Product Assets	
Operating Temperature	Maximum continuous 75°C and minimum -40°C without impact	Catalog [English]	
		Catalog Page [English]	
		Installation Manual [Spanish, French, English]	

