

HUBBELL
Wiring Device-Kellems

**Locking Devices, Twist-Lock®, Industrial,
Female Connector Body, 10A 250V/15A
125V, 3-Pole 3-Wire Non Grounding, Non-
NEMA, Screw Terminal and White**

By Hubbell Wiring Device-Kellems
Catalog # [HBL7555](#)

Locking Devices, Twist-Lock®, Industrial, Female Connector Body,
10A 250V/15A 125V, 3-Pole 3-Wire Non Grounding, Non-NEMA,
Screw Terminal, Black and White



Features

- Individually molded face for each blade configuration keeps debris out of plug interior
- Ribbed nylon housing is impact and chemical resistant
- Roomy wiring chamber provides ample space for wiring

Application

Heavy Duty Industrial

Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - Withstands 2,000V minimum, Environmental - Flammability - HB or better per UL94/CSA 22.2 No.0.17, Environmental - Operating Temperatures - Maximum Continuous 75°C Minimum -40°C (w/o impact), Mechanical - Terminal Accommodation - #18 AWG - #10 AWG stranded copper wire only., Mechanical - Terminal Identification - Terminals identified in accordance with UL 498

Specifications

Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	Yes

Conductor

Number Of Wires	3-Wire
Wire Size	#18 AWG to #10 AWG
Number Of Poles	3-Pole
Cable Range	0.296 - 0.625 in

Current

Amperage Rating	10/15 A
Voltage Rating Description	250/125 V
Dielectric Strength	Withstands 2,000V minimum
Current Rating	10 A
Voltage Rating	250/125 V
Connectivity	Pressure Terminal Screws
Current / Amperage Rating	10/15 A

Dimensions

Length	1.53 in
Display Size	Standard
Weight	0.15 lb.
Height	2.78 in
Width	1.53 in
Dimensions	1.53 in x 1.53 in x 2.78 in

General

Color	Black
Cord Range	• 0.296"-0.625"
Specifications	• Assembly Screws - Nickel plated brass • Clamp Plate - Zinc plated steel • Contacts - Copper alloy • Cord Clamps/Screws - Zinc plated steel • Housing - Phenolic • Terminal Screws - #5-40 Brass
UPC	783585237626
Type	Connector Body
Material - Mounting Hardware	Cord Mounted
Insulation	Insulated Body
Item Type	10A/15A Non-Grounding Insulgrip® Connector
Material	Phenolic

Logistics

Carton Quantity	10
-----------------	----

Operational

Temperature Rating	• Maximum Continuous: 75° C • Minimum Continuous: -40° C w/o impact, -25° with impact.
Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact

Product Assets

[Catalog \[English\]](#)
[Catalog Page \[English\]](#)

