

Locking Devices, Twist-Lock®, Industrial, Flanged Receptacle, 10A 250V/15A 125V, 3-Pole 3-Wire Non Grounding, Non- NEMA, Screw Terminal, Steel

By Hubbell Wiring Device-Kellems
Catalog # [HBL7557](#)

Locking Devices, Twist-Lock®, Industrial, Flanged Receptacle, 10A 250V/15A 125V, 3-Pole 3-Wire Non Grounding, Non- NEMA, Screw Terminal, Steel

Features

- Heat resistant thermoset construction
- Stainless steel casing
- #8-32 terminal screws
- Mounting screws included

Application

Heavy Duty Industrial

Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - Withstands 2,000V minimum, Environmental - Flammability - HB or better per UL94/CSA 22.2 No.0.17, Environmental - Moisture Resistance - IP20 Suitability, Environmental - Operating Temperatures - Maximum Continuous 75°C Minimum -40°C (w/o impact), Mechanical - Terminal Accommodation - #18 AWG -#10 AWG solid or stranded copper wire only., Mechanical - Terminal Identification - Terminals identified in accordance with UL 498

Specifications

Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	No
Industry Standard(s)	• Certified to CSA C22.2 No.42 • Fed. Spec. W-C-596 • Listed to UL 498

Conductor

Number Of Wires	3-Wire
Wire Size	#18 AWG to #10 AWG
Number Of Poles	3-Pole

Current

Amperage Rating	10/15 A
Voltage Rating Description	250/125 V
Dielectric Strength	Withstands 2,000V minimum



Current Rating	10 A
Voltage Rating	250/125 V
Connectivity	Screw Terminals
Phase	Single Phase
Current / Amperage Rating	10/15 A

Dimensions

Length	2.31 in
Display Size	Standard Sized Product
Weight	0.15 lb.
Height	1.32 in
Width	1.75 in
Dimensions	2.31 in x 1.75 in x 1.32 in

General

Specifications	• Blades - Brass • Flange - Stainless steel • Mounting Screw - Nickel plated brass • Terminal Screws - Brass
UPC	783585237664
Type	Receptacle
Material - Mounting Hardware	Screw Mounting
Item Type	10A/15A Non-Grounding Stainless Steel Flanged Receptacle
Material	Stainless Steel

Logistics

Carton Quantity	10
-----------------	----

Operational

Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
-----------------------	--

Product Assets

[Catalog \[English\]](#)
[Catalog Page \[English\]](#)