


Non-NEMA Twist-Lock Devices

Non-NEMA 10 Amp, 250 Volts, 15 Amp 125 Volts
3 Pole, 3 Wire, Non-Grounding and 2 Pole, 3 Wire, Grounding

For Replacement Use Only

IP20
SUITABILITY


Plugs

Description	Cord Dia.	Catalog Number	
Black and white nylon. Multiple drive screws.	.230"-.720" (5.8-18.3)	HBL7567C	—
Yellow and white nylon. Multiple drive screws.	.230"-.720" (5.8-18.3)	HBL7567CY	—


Note: See page C-51 for accessories.

Flanged Inlets

Description	Catalog Number	
Stainless steel casing.	HBL7556	HBL7556G




HBL7567C



HBL7556

For Replacement Use Only

IP20
SUITABILITY

Connector Bodies

Description	Cord Dia.	Catalog Number	
Insulgrip® connector, black and white nylon. Multiple drive screws.	.230"-.720" (5.8-18.3)	HBL7565C	—
Insulgrip connector, yellow and white nylon. Multiple drive screws.	.230"-.720" (5.8-18.3)	HBL7565CY	—
Black phenolic.	.296"-.625" (7.5-15.9)	HBL7555	HBL7555G

Note: See page C-51 for accessories.




HBL7565C

Receptacles

Description	Catalog Number	
Duplex, black RTP*, back and side wired.	HBL7580	HBL7580G
Single, black phenolic, back and side wired.	HBL7582	HBL7582G

Note: See page C-50 for accessories.




HBL7580

Flanged Receptacles

Description	Catalog Number	
Stainless steel casing.	HBL7557	HBL7557G

Note: *RTP is an abbreviation for reinforced thermoplastic.

The devices shown on this page are not listed by Underwriters Laboratories Inc. and are for replacement use only in existing installations.



HBL7557

CAUTION: To avoid electrical shock, review premises carefully and do not use if slot or blade configuration (design) is already in a circuit having a rating differing from the rating of this device.

Dimensions in Inches (mm)