

HUBBELL
Wiring Device-Kellems

**Locking Devices, Twist-Lock®, Industrial,
Single Flush Receptacle, 10A 250V, 15A
125V, 3-Pole 3-Wire Non-Grounding, Non-
NEMA, Screw Terminal Phenolic.**

By Hubbell Wiring Device-Kellems
Catalog # [HBL7582](#)

Locking Devices, Twist-Lock®, Industrial, Single Flush Receptacle,
10A 250V, 15A 125V, 3-Pole 3-Wire Non-Grounding, Non-NEMA,
Screw Terminal, Black Phenolic.



Features

- Thermoset construction offers high heat resistance
- High performance copper alloy contacts
- Corrosion resistant zinc plated steel one-piece mounting strap

Application

Heavy Duty Industrial

Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - Withstands 2,000V minimum, Environmental - Flammability - HB or better per UL94/CSA 22.2 No.0.17, Environmental - Moisture Resistance - IP20 Suitability, Environmental - Operating Temperatures - Maximum Continuous 75°C Minimum -40°C (w/o impact), Mechanical - Terminal Accommodation - #18 AWG -#10 AWG solid or stranded copper wire only., Mechanical - Terminal Identification - Terminals identified in accordance with UL 498

Specifications


Standards - RoHS Compliance Status	CM
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	Yes
Industry Standard(s)	• Certified to CSA C22.2 No.42 • Fed. Spec. W-C-596 • Listed to UL 498

Conductor

Number Of Wires	3-Wire
Wire Size	#18 AWG to #10 AWG
Number Of Poles	3-Pole

Current

Amperage Rating	10/15 A
Voltage Rating Description	250/125 V
Dielectric Strength	Withstands 2,000V minimum
Current Rating	10 A



Voltage Rating	250/125 V
Connectivity	Back and Side Wired Screw Terminals
Phase	Single Phase
Current / Amperage Rating	10/15 A

Dimensions

Length	3.28 in
Display Size	Standard Sized Product
Weight	0.15 lb.
Height	1.19 in
Width	1.5 in
Dimensions	3.28 in x 1.5 in x 1.19 in

General

Color	Black
Specifications	• Base - Molded Thermoset • Clamp - Brass • Contacts - Brass • Face - RTP • Ground Contact - Brass • Terminal Screws - Brass
UPC	783585237718
Type	Receptacle
Material - Mounting Hardware	Screw Mounting
Item Type	10A/15A Single Receptacle
Material	Phenolic

Logistics

Carton Quantity	10
-----------------	----

Operational

Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
-----------------------	--

Product Assets

Catalog [English]
Catalog Page [English]
Catalog Page [English]
Installation Manual [English]