

Locking Devices, Midget Twist-Lock®, Industrial, Female Straight Connector, 15A 125V AC, 2-Pole 3-Wire Grounding, NEMA ML-2R, Screw Terminal, Black.

By Hubbell Wiring Device-Kellems
Catalog # [HBL7593](#)

Locking Devices, Midget Twist-Lock®, Industrial, Female Straight Connector, 15A 125V AC, 2-Pole 3-Wire Grounding, NEMA ML-2R, Screw Terminal, Black.

Features

- Abuse resistant nylon housing
- Phenolic body for high heat resistance
- Angled body design for low profile in tight spaces

Application

Heavy Duty Industrial

Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - Withstands 2,000V minimum, Environmental - Flammability - HB or better per UL94/CSA 22.2 No.0.17, Environmental - Moisture Resistance - IP20 Suitability, Environmental - Operating Temperatures - Maximum Continuous 75°C Minimum -40°C (w/o impact), Mechanical - Terminal Accomodation - #18 AWG - #14 AWG stranded copper wire only., Mechanical - Terminal Identification - Terminals identified in accordance with UL 498

Specifications

Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	Yes
Nema Rating	ML-2R
Industry Standard(s)	• Certified to CSA C22.2 No.42 • Listed to UL 498

Conductor

Number Of Wires	3-Wire
Wire Size	#18 AWG to #14 AWG
Number Of Poles	2-Pole
Cable Range	0.281 - 0.421 in
Conductor Range	#14 AWG to #12 AWG

Current

Amperage Rating	15 A
Voltage Rating Description	125 V
Dielectric Strength	Withstands 2,000V minimum
Current Rating	15 A
Voltage Rating	125 V



Connectivity	Pressure Terminal Screws
Current / Amperage Rating	15 A
Dimensions	
Length	1.17 in
Display Size	Midget Locking
Weight	0.10 lb.
Height	2.42 in
Width	1.17 in
Dimensions	1.17 in x 1.17 in x 2.42 in
General	
Color	Black
Cord Range	0.281"-0.421"(7.1-10.7)
Specifications	• Blades - Brass • Contact Holder - Phenolic • Housing - Nylon • Terminal Clamp - Zinc plated steel with black lacquer finish • Terminal Screws - #5-40 Brass
UPC	783585237749
Type	Connector Body
Material - Mounting Hardware	Cord Mounted
Insulation	Insulated Body
Item Type	15A Midget Twist-Lock® Connector
Material	Nylon
Logistics	
Pallet Quantity	6000
Carton Quantity	10
Operational	
Temperature Rating	• Maximum Continuous: 75° C • Minimum Continuous: -40° C w/o impact, -25° with impact.
Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact

Product Assets

[Catalog \[English\]](#)

[Catalog Page \[English\]](#)

[Installation Manual \[English\]](#)



A Hubbell brand