

HUBBELL
Wiring Device-Kellems

**Locking Devices, Twist-Lock®, Industrial,
Flanged Receptacle, 20A 250V, 2-Pole 2-
Wire Non Grounding, L2-20R, Screw
Terminal, White**

By Hubbell Wiring Device-Kellems
Catalog # [HBL8809C](#)

Locking Devices, Twist-Lock®, Industrial, Flanged Receptacle,
20A 250V, 2-Pole 2-Wire Non Grounding, L2-20R, Screw
Terminal, White



Features

- Impact resistant thermoplastic construction
- Backwired terminations for ease of installation
- #8-32 Multiple drive terminal screws (Slotted, Phillips, Robertson)
- Mounting screws included

Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - Withstands 2,000V minimum, Environmental - Flammability - HB or better per UL94/CSA 22.2 No.0.17, Environmental - Moisture Resistance - IP20 Suitability, Environmental - Operating Temperatures - Maximum Continuous 75°C, Minimum -40°C (w/o impact), Mechanical - Terminal Accommodation - #16 - #10 AWG solid or stranded copper wire only., Mechanical - Terminal Identification - Terminals identified in accordance with UL 498

Specifications


Standards - RoHS Compliance	CM
Status	
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	Yes
Nema Rating	L2-20R
Industry Standard(s)	Fed.Spec.W-C-596

Conductor

Number Of Wires	2-Wire
Wire Size	#16 AWG to #10 AWG
Number Of Poles	2-Pole

Current

Amperage Rating	20 A
Voltage Rating Description	250 VAC
Dielectric Strength	Withstands 2,000V minimum
Current Rating	20 A
Voltage Rating	250 VAC
Connectivity	Back and Side Wired Screw Terminals
Phase	Single Phase
Current / Amperage Rating	20 A



Dimensions

Length	2.56 in
Display Size	Standard Sized Product
Weight	0.10 lb.
Height	1.72 in
Width	2.56 in
Dimensions	2.56 in x 2.56 in x 1.72 in

General

Color	White
Specifications	• Assembly Screws - Steel - zinc plated • Contacts - Brass • Housing - Nylon • Mounting Screw - Nickel plated brass • Terminal Clamp - #8-32 Brass (Phillips / Slotted / Robertson) • Terminal Clamp - Cold rolled steel - nickel plated • Terminal Retainer - Clear polycarbonate
UPC	783585180601
Type	Flanged Receptacle
Material - Mounting Hardware	Screw Mounting
Item Type	Flanged Receptacles
Material	Nylon

Logistics

Carton Quantity	10
-----------------	----

Operational

Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
-----------------------	--

Product Assets

- [Catalog \[English\]](#)
- [Catalog Page \[English\]](#)
- [Catalog Page \[English\]](#)
- [Installation Manual \[Spanish, French, English\]](#)