

Locking Devices, Twist-Lock®, Industrial, Flanged Inlet, 20A 250V, 2-Pole 2-Wire Non Grounding, L2-20P, Screw Terminal, White

By Hubbell Wiring Device-Kellems
Catalog # [HBL8815C](#)

Locking Devices, Twist-Lock®, Industrial, Flanged Inlet, 20A 250V, 2-Pole 2-Wire Non Grounding, L2-20P, Screw Terminal, White

Features

- Impact resistant thermoplastic construction
- Backwired terminations for ease of installation
- #8-32 Multiple drive terminal screws (Slotted, Phillips, Robertson)
- Mounting screws included

Application

Extra Heavy Duty Industrial

Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - Withstands 2,000V minimum, Environmental - Flammability - HB or better per UL94/CSA 22.2 No.0.17, Environmental - Operating Temperatures - Maximum Continuous 75°C, Minimum -40°C (w/o impact), Mechanical - Terminal Accommodation - #16 AWG - #8 AWG solid or stranded copper wire only., Mechanical - Terminal Identification - Terminals identified in accordance with UL 498

Specifications

Standards - RoHS Compliance Status	CM
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	Yes
Nema Rating	L2-20P
Industry Standard(s)	Fed.Spec.W-C-596

Conductor

Number Of Wires	2-Wire
Wire Size	#16 AWG to #8 AWG
Number Of Poles	2-Pole

Current

Amperage Rating	20 A
Voltage Rating Description	250 VAC
Dielectric Strength	Withstands 2,000V minimum
Current Rating	20 A
Voltage Rating	250 VAC
Connectivity	Screw Terminals
Phase	Single Phase



Current / Amperage Rating	20 A
Dimensions	
Length	2.56 in
Display Size	Standard Sized Product
Weight	0.15 lb.
Height	1.72 in
Width	2.56 in
Dimensions	2.56 in x 2.56 in x 1.72 in
General	
Color	White
Specifications	• Assembly Screws - Steel - zinc plated • Blades - Brass • Housing - Nylon • Mounting Screw - Nickel plated brass • Terminal Clamp - Cold rolled steel – nickel plated • Terminal Retainer - Clear polycarbonate • Terminal Screws - #8-32 Brass (Phillips / Slotted / Robertson)
UPC	783585180755
Type	Flanged Inlet
Material - Mounting Hardware	Screw Mounting
Insulation	Insulated Body
Item Type	20A Insulgrip® Flanged Inlet
Material	Nylon
Logistics	
Carton Quantity	10
Operational	
Temperature Rating	• Maximum Continuous: 75° C • Minimum Continuous: -40° C w/o impact, -25° with impact.
Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
Horsepower - Maximum	2

Product Assets

[Catalog \[English\]](#)

[Catalog Page \[English\]](#)

[Catalog Page \[English\]](#)

[Installation Manual \[Spanish, French, English\]](#)



A Hubbell brand