

Straight Blade Devices, Male Plug, Nylon,
4-Position, Heavy Duty,
Industrial/CommercialGrade, Angled, 3-
Pole 4-Wire Grounding, 30A 125/250V, 14-
30P.

By Hubbell Wiring Device-Kellems
Catalog # [HBL9432C](#)

Straight Blade Devices, Male Plug, Nylon, 4-Position, Heavy Duty,
Industrial/CommercialGrade, Angled, 3-Pole 4-Wire Grounding,
30A 125/250V, 14-30P , Black, Single Pack.

Features

- **Material & Construction:** Crafted from industrial-grade nylon, this durable plug withstands daily use, ensuring long-lasting, reliable performance essential for EV charging system integrity.
- **Configuration:** Includes a 4-position, angled layout with 3 poles and 4 wires, grounding included. It meets EV charging’s high demands and boosts safety by reducing electrical hazards.
- **Electrical Rating:** Boasting a 50A, 125/250V capacity, this plug is suited for high-powered EV charging stations, ensuring efficient and reliable power delivery.
- **Safety Compliance:** This plug meets strict safety standards with a grounding pin and heavy-duty materials, reducing electrical shock risks and ensuring a secure connection to protect equipment and users.
- **Ease of Use:** Designed with an angled interface and ergonomic handle, this plug allows easy operation and handling in tight spaces, ensuring safe and effortless insertion and removal.
- **Long-Term Reliability:** Investing in Hubbell’s Straight Blade Male Plug means choosing a product that will not only meet the current demands of EV charging but also continue to deliver performance and safety long into the future.

Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - Withstands 2,000V minimum, Environmental - Flammability - UL 94 HB, Environmental - IP Suitability - IP20, Environmental - Operating Temperatures - Maximum continuous 75°C, minimum -40°C (w/o impact), Mechanical - Product Identification - Ratings are a permanent part of the device, Mechanical - Terminal Accommodation - #12 AWG through #4 AWG copper wire only, Mechanical - Terminal Identification - Terminals identified in accordance with UL 498 and CSA

Specifications

EU RoHS Indicator	Contact Manufacturer
Industry Standard(s)	• Certified to CSA • UL Listed File E1706



Nema Rating	14-30P
Conductor	
Number Of Wires	4-Wire
Wire Size	#12 AWG to #4 AWG
Number Of Poles	3-Pole
Current	
Dielectric Strength	Withstands 2,000V minimum
Current Rating	30 A
Amperage Rating	30 A
Voltage Rating Description	125/250 V
Current / Amperage Rating	30 A
Wattage	7500 W
Voltage Rating	• 125 V • 250 V
Dimensions	
Length	4.5 in
Width	3.38 in
Weight	0.8 lb.
Height	2.37 in
Dimensions	4.5 in x 3.38 in x 2.37 in
General	
Series	Extra Heavy Duty
OEM Brand Name	Hubbell Wiring Device-Kellems
Cord Range	0.625"-1.310"
Style	Grounding
Color	Black
Type	Plug
Material	Nylon
Specifications	• Blade Holder - Reinforced Thermoplastic Polyester • Blades - Brass • Box Terminals - Copper Alloy • Cord Clamps - Reinforced Thermoplastic Polyester • Housing - Supertough Nylon
UPC	783585015446

Logistics

Carton Quantity	5
Pallet Quantity	765

Operational

Operating Temperature	Maximum continuous 75°C and minimum -40°C without impact
-----------------------	---

Horsepower - Maximum 2

Product Assets

- [Catalog \[English\]](#)
- [Catalog Page \[English\]](#)
- [Installation Manual \[Spanish, French, English\]](#)



A Hubbell brand