



LINKOSITY® Feed - UL Type 4X Rated**
4X Rated NEMA Standard Items



Description	Catalog Number
20A 125V Straight Blade†	MLWF2010
20A 125V WTSSTL.	MLWF2020
20A 125V Straight Blade, Pass-Thru.	MLWF201P
20A 125V WTSSTL, Pass-Thru.	MLWF202P
20A 125/250V WTSSTL, No Pass-Thru.	MLWF2070
30A 125V WTSSTL, No Pass-Thru.	MLWF1050
30A 250V WTSSTL, No Pass-Thru.	MLWF1060
30A 125V WTSSTL, No Pass-Thru.	MLWF2050
30A 250V WTSSTL, No Pass-Thru.	MLWF2060

Note: †Straight Blade are UL Type 4X when not in use only.

Device Type	Style	Type	No. of Devices	Device Type	Pass-Thru
M	L = LINKOSITY	WF = Watertight Safety-Shroud Receptacle WM = Watertight Safety-Shroud Inlet	1 2	01 = 20A 125V Straight Blade† 02 = 20A 125V Twist-Lock 03 = 20A 250V Twist-Lock 04 = 20A 277V Twist-Lock 05 = 30A 125V Twist-Lock 06 = 30A 250V Twist-Lock 07 = 20A 125/250V Twist-Lock 08 = 20A 3Ø 250V Twist-Lock 09 = 20A 3Ø 480V Twist-Lock 10 = 30A125/250V Twist-Lock 11 = 30A 3Ø 250V Twist-Lock 12 = 30A 3Ø 480V Twist-Lock 13 = 30A 3Ø 600V Twist-Lock	P = Pass-Thru O = No Pass-Thru

All LINKOSITY - UL Type 4X Rated•
4X Rated LINKOSITY Standard Items

Description	Catalog Number
20A 3W up to 600V, 4 Port.	M4L2003PB0
20A 3W up to 600V, 4 Port Pass-Thru.	M4L2003BPB

Note: †Straight Blade are UL Type 4X when not in use only.



Conduit Feed - UL Type 4X Rated**
Conduit Feed Standard Items

Description	Catalog Number
20A 125V Straight Blade.	MCWF2010
20A 125V WTSSTL.	MCWF2020
20A 250V WTSSTL.	MCWF2030
20A 277V WTSSTL.	MCWF2040
30A 125V WTSSTL.	MCWF2050
30A 250V WTSSTL.	MCWF2060
20A 125/250V WTSSTL.	MCWF2070
20A 3Ø, 250V WTSSTL.	MCWF2080
20A 3Ø, 480V WTSSTL.	MCWF2090
30A 125/250V WTSSTL.	MCWF2100
30A 3Ø 250V WTSSTL.	MCWF2110
30A 3Ø 480V WTSSTL.	MCWF2120
30A 3Ø 600V WTSSTL.	MCWF2130

Note: **Watertight Safety-Shroud® Twist-Lock® Plug required when in use.
•Closure cap required when not in use.
Accepts PH2304 series cables.
WTSSTL is an abbreviation for Watertight Safety-Shroud® Twist-Lock®.

Device Type	Style	Type	No. of Poles	Conductor Colors	Pass - Thru
M	4L - LINKOSITY	20 - 20A 23 - 20A Super Neutral Isolated Ground 30 - 30A	02 03 04 05 06	PA - Green/Yellow Black (all others) PB - Green/Yellow White Black (all others)	P - Pass-Thru O - No Pass-Thru



Device Type	Style	Type	No. of Devices	NEMA Device Type	Pass-Thru
M	C - Conduit Feed	WF - Watertight Safety-Shroud Receptacles WM - Watertight Safety-Shroud Inlet	2	01 - 20A 125V Straight Blade 02 - 20A 125V Twist-Lock 03 - 20A 250V Twist-Lock 04 - 20A 277V Twist-Lock 05 - 30A 125V Twist-Lock 06 - 30A 250V Twist-Lock 07 - 20A 125/250V Twist-Lock 08 - 20A 3Ø 250V Twist-Lock 09 - 20A 3Ø 480V Twist-Lock 10 - 30A125/250V Twist-Lock 11 - 30A 3Ø 250V Twist-Lock 12 - 30A 3Ø 480V Twist-Lock 13 - 30A 3Ø 600V Twist-Lock	O - No Pass-Thru

Replacement Mounting Feet

Description	Catalog Number
For power distribution assemblies.	HBLRFT1*

Note: * Package of 10 mounting feet and 10 screws.

Dimensions in Inches (mm)

