

## Industrial Grade, Motor Disconnect Switch, Unfused, 3 Pole, 30A 600V AC, Screw Terminals, IP69k, NEMA Type 4X, 12 Non-Metallic Sloped Top Enclosure

By Hubbell Wiring Device-Kellems  
Catalog # [HBLDS30](#)

Industrial Grade, Motor Disconnect Switch, Unfused, 3 Pole, 30A 600V AC, Screw Terminals, IP69k, NEMA Type 4X, 12 Non-Metallic Sloped Top Enclosure



### Features

- Constructed from corrosion and impact resistant UV stabilized non-metallic material+M4:T4
- Rounded sloped top enclosure supports best practices in hygienic design by shedding dirt and debris
- IP69k and Type 4X,12K water ingress protection and Certified by NSF for hygiene in food processing applications
- Highly visible red handle can be locked in the OFF position as a method of compliance with OSHA Lockout/Tagout requirements
- Product rating are permanently laser-marked and will not wash off
- Highly visible red handle can be locked in the OFF position as a method of compliance with OSHA Lockout/Tagout requirements
- Accepts up to 2 Auxiliary contacts(HBLAC1 and/or HBLAC2 ) or 3 when HBLAC11 is used with either a HBLAC1 or HBLAC2.

### Application

Heavy Duty Industrial and/or Washdown

### Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current & voltage, Electrical - Dielectric Voltage - Withstands 3000V AC minimum, Electrical - Max. Working Voltage - 600V AC RMS, Environmental - Flammability - UL94-5VA and V0 Classification, Environmental - Operating Temperature - Max Continuous 75°C,Min Continuous -40°C w/o impact, Environmental - UV Resistance - All materials are UV stabilized, Mechanical - Impact Resistance - In accordance with UL 746C, Mechanical - Mounting - Non-Metallic - External fully adjustable feet, Mechanical - Product Identification - Identification and ratings are part of external label, Mechanical - Terminal Identification - In accordance with UL, CSA and international conventions

### Specifications

Industry Standard(s) cULus Listed  
Environmental Conditions Indoor and Outdoor

### Conductor

Wire Size #14 AWG to #8AWG

### Configuration

Mounting Method External fully adjustable feet

### Current

Dielectric Strength Withstands 3000V AC minimum  
Current / Amperage Rating 30 A

### Dimensions

Hub Size 3/4"  
Weight 2.6 lb.  
Height 4.12 in

### General

Material - Mounting Hardware Stainless Steel Screw Mounting  
Type Disconnect Switches  
Enclosure Type IP69k and UL Type 4X, 12  
Series Non-Fused

- Specifications
- Base - Valox®
  - Enclosure Gasket - Neoprene
  - Handle - Valox®
  - Shaft (Unfused) - Valox®
  - Top - Valox®

UPC 783585763002  
Ingress Protection IP69k and UL NEMA Type 4X, 12  
Style Heavy Duty  
Color Gray

### Operational

Operating Cycles 10,000 Cycles Minimum  
Operating Temperature Without Impact Maximum continuous 75°C and minimum -40 °C  
Horsepower - Maximum 15

## Product Assets

[Catalog Page \[English\]](#)

[Catalog Page \[English\]](#)

[Catalog Page \[English\]](#)

[Installation Manual \[English\]](#)

---



A Hubbell brand

© 2025 Hubbell Incorporated. All rights reserved  
WDK-HBLDS30-SPEC-EN | REV 12/2025