HUBBELL
Wiring Device-Kellems

Switches and Lighting Controls, Industrial Grade, Disconnect Switches, Replacement Switch, Three Pole, 60A 600V AC, Screw Terminals, Gray



By Hubbell Wiring Device-Kellems
Catalog # HBLDS60100RS

Switches and Lighting Controls, Industrial Grade, Disconnect Switches, Replacement Switch, Three Pole, 60A 600V AC, Screw Terminals, Gray

Features

- Industrial Grade
- Disconnect Switches
- Replacement Switch
- Three Pole

Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - Withstand 3,000V AC, Electrical - Max Working Voltage - 600V AC RMS, Environmental - Flammability - UL94-5VA and V-0 classification, Environmental - Ingress Protection - IP67 Suitability, Environmental - Operating Temperatures - Max Continuous- 75 °C, Minimum -40 ° w/o Impact, Mechanical - Impact Resistance - In accordance with UL746C, Mechanical - Product Identification - Identification and ratings are a part of the external label and molded into the receptacle mount., Mechanical - Terminal Identification - Terminals identified in accordance with North American and International conventions

Specifications

Standards - RoHS Compliance Status	CM
EU RoHS Indicator	No
Industry Standard(s)	UL Listed

Current

Amperage Rating	60/100 A
Dielectric Strength	Withstands 3000V AC minimum
Current / Amperage Rating	60/100 A

General

Color	Gray
Style	Replacement Switches
Ingress Protection	IP67
Series	• Non-Fused • Fused
Specifications	• Assembly Screws - Stainless Steel • Gaskets - Neoprene • Hinge Spring - Stainless Steel • Interlock Items - Replacement Parts
UPC	783585955216
Type	Accessories

Logistics

Pallet Quantity	720
Carton Quantity	10

Operational

Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact

Product Assets

Catalog [English]
Catalog Page [English]
Catalog Page [English]
Installation Manual [French]

© 2026 Hubbell Incorporated. All rights reserved