

# 15A Twist-Lock Devices

15 Amp, 125, 250 Volts  
and 277 Volts AC

**IP20**  
SUITABILITY



## Plugs

Description	Cord Dia.	Catalog Number		
		15A 125V NEMA L5-15P 0.5 HP	15A 250V NEMA L6-15P 1.5 HP	15A 277V AC NEMA L7-15P 2 HP
Insulgrip® plug, black and white nylon. Multiple drive screws. Fed Spec WC596.	.230"-.720" (5.8-18.3)	HBL4720C	HBL4570C	HBL4770C
Insulgrip plug, black and white, spring termination. Fed Spec WC596.	.230"-.720" (5.8-18.3)	HBL4720CST	HBL4570CST	HBL4770CST
All black nylon.	.230"-.720" (5.8-18.3)	HBL4720CBK	—	—
Insulgrip angle plug, 8 position angle, black and white nylon. Multiple drive screws.	.325"-.655" (8.3-16.6)	HBL4720CA	HBL4570CA	HBL4770CA
Insulgrip plug, corrosion resistant, yellow and white nylon. Multiple drive screws. Fed Spec WC596.	.230"-.720" (5.8-18.3)	HBL47CM20C	HBL45CM70C	HBL47CM70C
Elastogrip® plug, yellow elastomer, dust tight.	300"-.655" (7.6-16.6)	HBL2447	—	—
Elastogrip plug, yellow elastomer, water/dust tight.	300"-.655" (7.6-16.6)	HBL24W47	—	—
Valise® plug, yellow nylon.	.220"-.660" (5.6-16.8)	HBL4723VY	HBL4573VY	HBL4773VY
Valise plug, black nylon.	.220"-.660" (5.6-16.8)	HBL4723VBK	HBL4573VBK	HBL4773VBK

Note: See page C-51 for accessories.

## Flanged Inlets

Description	Catalog Number		
Insulgrip flanged inlet, nylon casing, back wired.	HBL4716C	HBL4586C	HBL4786C
Stainless steel casing, brown phenolic.	HBL4716*	HBL4586*	HBL4786*
Corrosion resistant, stainless steel casing, yellow melamine.	HBL47CM16*	—	—

Note: See page C-50 for accessories. HP ratings are AC only. Only plugs are HP rated.

See page C-69 for technical information on Insulgrip devices.

\*These flanged inlets will not accept Valise® connector bodies.



HBL4720C



HBL4720CA



HBL24W47



HBL4723VY



HBL4716C



HBL4716

Dimensions in Inches (mm)