

Ordering Information Notes:

1. Common use sizes are listed below. Contact factory for other configurations or see page V-3 for Range of Offering table.
2. Trench Duct part numbers are for reference only. All Trench Duct orders are lot billed with a generic TW prefix project specific part number. Please contact your local Hubbell Territory Manager for all Hubbell Duct quotations.



Trench Duct

Description	Trench Depth	Cover Width	No. of Compartments	Catalog Number	
Straight Section Manufactured in standard 6' lengths with factory installed dividers. Provided with (3) leveling feet/couplers on each side, (3) 24" long cover plates and (3) cover plate joint protectors. Leveling feet permit 1" of vertical pre-pour adjustment. Consult factory for additional vertical adjustment.	2-1/2" 3" 2-1/2" 3" 2-1/2" 3" 2-1/2" 3"	9" 9" 12" 12" 18" 18" 24" 24"	1 2 2 3 3 4 3 4	OKA/B9-1C-1/4 OKA/C9-2C-1/4 OKA/B12-2C-1/4 OKA/C12-3C-1/4 OKA/B18-3C-1/4 OKA/C18-4C-1/4 OKA/B24-3C-1/4 OKA/C24-4C-1/4	

Note: For Aluminum Trench Duct or Fittings, add "AL" suffix to catalog number.

Fittings

Description	Outside Cover	No. of Compartments	Catalog Number	
Horizontal "L" Fitting Manufactured with a single cover and matching internal partitions to form a 90° horizontal "L". Includes cover plate joint protectors and leveling feet.	12" x 12" 12" x 12" 15" x 15" 15" x 15" 21" x 21" 21" x 21" 27" x 27" 27" x 27"	1 2 2 3 3 4 3 4	OKL/B9-1C-1/4 OKL/C9-2C-1/4 OKL/B12-2C-1/4 OKL/C12-3C-1/4 OKL/B18-3C-1/4 OKL/C18-4C-1/4 OKL/B24-3C-1/4 OKL/C24-4C-1/4	
Horizontal 45° Elbow Fitting Manufactured with a split cover plate and matching internal partitions to form a 45° Mitered "L". Other angles available. Includes cover plate joint protectors and leveling feet.	45° 45° 45° 45° 45° 45° 45°	1 2 2 3 3 4 3 4	OKL45/B9-1C-1/4 OKL45/C9-2C-1/4 OKL45/B12-2C-1/4 OKL45/C12-3C-1/4 OKL45/B18-3C-1/4 OKL45/C18-4C-1/4 OKL45/B24-3C-1/4 OKL45/C24-4C-1/4	
Single Level "T" Junction Fitting Manufactured with matching internal partitions and crossovers to isolate power and communications. Includes cover plate joint protectors and leveling feet.	15" x 12" 15" x 12" 18" x 15" 18" x 15" 24" x 21" 24" x 21" 30" x 27" 30" x 27"	1 2 2 3 3 4 3 4	OKT/B9-1C-1/4 OKT/C9-2C-1/4 OKT/B12-2C-1/4 OKT/C12-3C-1/4 OKT/B18-3C-1/4 OKT/C18-4C-1/4 OKT/B24-3C-1/4 OKT/C24-4C-1/4	
Pull Box Manufactured to attach to trench section replacing end cap. Divided into compartments as required. Additional depth permits attachment of large conduits. Box is field punched for conduits. Standard depth is 6." Also available as a stand-alone SPOKB solid-sided floor box with trench rails on all 4 sides. Consult factory for details.	9" x 12" 9" x 12" 12" x 12" 12" x 12" 18" x 12" 18" x 12" 24" x 12" 24" x 12"	1 2 2 3 3 4 3 4	OKB/B9-1C-1/4 OKB/C9-2C-1/4 OKB/B12-2C-1/4 OKB/C12-3C-1/4 OKB/B18-3C-1/4 OKB/C18-4C-1/4 OKB/B24-3C-1/4 OKB/C24-4C-1/4	

Exit Cover Fittings

Description	Trench Width	Catalog Number	
Exit Cover Designed to provide exit and feed for Trench Duct. Conduit openings are provided for power and communication exit or feed using conventional conduit fittings or service fittings. Exit Cover may be placed anywhere along the length of the trench. All Exit Covers are 6" long. Hole sizes and placement are specified at time of order.	9" 12" 18" 24"	OKC/9-xx OKC/12-xx OKC/18-xx OKC/24-xx	
Access Hood Similar to Exit Cover except provided with a louvered opening for communication cables. Consult factory for custom Access Hoods.	9" 12" 18" 24"	OKHOOD-9 OKHOOD-12 OKHOOD-18 OKHOOD-24	

Dimensions in Inches (mm)