



- Available with up to 4 receptacles, wide variety of NEMA receptacle types
- LINKOSITY® power pass through option
- Fed with LINKOSITY power cable and receptacle
- Metal enclosure ANSI 61 gray powder coat NEMA 1
- Device identification marking
- Versatile mounting provision
- Accepts PH230X series cables



Straight Blade - UL Type 1

Device Type	Switch Types	# Recepts	Receptacle Type	Receptacle Feature	Pass-thru	Custom Configurations*
M	SL = Switch Local SM = Switch Master OO = No Switch	1 2 3 4	SG = Spec Grade HG = Hospital Grade CR = Corrosion Resistant	IG = Isolated Ground GF = Ground Fault OO = Standard	P = Pass-thru** O = No Pass-thru	D = 2 Circuit A = A Phase B = B Phase C = C Phase
Example: M	SL	1	SG	OO	P	

Twist-Lock® - UL Type 1

Device Type	Switch Types	# Recepts	Receptacle Type	Receptacle Feature	Pass-thru	Custom Configurations*
M	SL = Switch Local SM = Switch Master OO = No Switch	1 2 3 4	L1 = 15A L2 = 20A	IG = Isolated Ground OO = Standard	P = Pass-thru O = No Pass-thru	6 = 250V
Example: M	OO	3	L1	IG	O	

Note: Local switches control all receptacles in a box. Master switches control local and downstream receptacles.
Consult factory for alternate wiring schemes.
*Consult factory for wiring specifications and connecting cables.
**Pass-thru on phase tap boxes are 3Ø.

Switch Only (ON/OFF) - UL Type 1

Device Type	Switch Types	Switch Style	Poles
S	1 = 1 Gang 2 = 2 Gang 3 = 3 Gang	2W = ON/OFF	1P = Single Pole 2P = Two Pole
Example: S	1	2W	1P

Switch Only (4-Way) - UL Type 1

Device Type	Switch Types	Switch Style
S	1 = 1 Gang	4W = 4 Way
Example: S	1	4W

Switch Only (3-Way) - UL Type 1

Device Type	Switch Types	Switch Style	Position
S	1 = 1 Gang	3W = 3 Way	M = Main R = Remote LM = Line to Main LR = Load to Remote
Example: S	1	3W	M

Note: For use with Px2304PBxxx series cables.

Features

Receptacle Types		CR	HG	SG	L1
OO	Standard	HBL53CM62	HBL8300STGY	5362STGY	HBL4700ST
IG	Isolated Ground	—	—	CR5352IGGY	IG4700AST
GF	Ground Fault	—	GFR83GRY	GFRST20GY	—
SS	—	—	—	—	—
Switch Types		CR	HG	SG	L1
SL	Local ON/OFF	—	—	HBL1221STILR	—
SM	Master ON/OFF	—	—	HBL1221STILR	—

Dimensions in Inches (mm)