



LINKOSITY® UL Type 3R and 4X Rated Assemblies

- Available with switch, ground fault, corrosion resistant or isolated ground receptacle types
- LINKOSITY power pass through option
- Fed with LINKOSITY power cable and receptacle
- UL Type 3R and 4X Rated
- Device identification marking
- Versatile mounting provision



LINKOSITY Feed - UL Type 3R Rated*

3R Rated Standard Items

Description	Catalog Number
20A 125v ground fault.	M3R002SGGF0
20a 125v switched, spec grade.	M3RSL1SG000
20a 125v switched, ground fault.	M3RSL1SGGF0
20a 125v spec grade.	M3R002SG000
20a 125v ground fault, pass-thru.	M3R002SGGFP
20a 125v switched, spec grade, pass-thru.	M3RSL1SG00P
20a 125v switched, ground fault, pass-thru.	M3RSL1SGGFP
20a 125v (2) switches.	M3R2SG000
20a 125v 1-gang ground fault.	M3R001SGGF0
20a 125v corrosion resistant.	M3R002CR000
20a 125v isolated ground.	M3R002SGIGP
20a 125v spec grade, pass-thru.	M3R002SG00P

Note: *When cover closed.



Device Type	Style	Type	No. of Devices	Device Type	Device Feature	Pass-Thru
M	3R = 3R Lids 3D = 3R Deep Cover	SL = Switch Local SM = Switch Master OO = None	1 2	SG = Spec Grade HG = Hospital Grade CR = Corrosion Resistant L1 = 15A Locking	IG = Isolated Ground GF = Ground Fault SI = Surge/IG SS = Surge OO = Standard	P = Pass = Thru O = No Pass = Thru
Example: M	3D	SM	2	CR	OO	O

Replacement Mounting Feet

Description	Catalog Number
For Power Distribution Assemblies.	HBLRFT1*

Note: *Package of 10 mounting feet and 10 screws.



Dimensions in Inches (mm)