

Hubbell-PRO, Motor Disconnect Switch,
Unfused, 3 Pole, 30A 600V AC, Screw
Terminals, IP67, NEMA 4X, 12 Non-Metallic
Enclosure

By Hubbell Wiring Device-Kellems
Catalog # [HPD30](#)

30A Enclosed Motor Disconnect

Features

- UL 508 / UL 60947-4-1 “Suitable as a motor Disconnect”
- IP67 and Type 4X thermoplastic enclosure
- Highly visible yellow OSHA LO/TO Handle
- Moveable mounting feet
- Stainless steel captive screws
- Non-Fused
- Accepts up to 2 Auxiliary contacts

Application

Labelless

Specifications

Nema Rating	NEMA 4
Buy America(n) Qualified	TAA Compliant (All status valid till December 2026)
Industry Standard(s)	• cULus Certified • CE Certified
Environmental Conditions	Indoor and Outdoor

Conductor

Number Of Poles	3
-----------------	---

Configuration

Mounting Method	4 FEET INCLUDED
-----------------	-----------------

Current

Frequency Rating	60 Hz
Amperage Rating	30 A



Dielectric Strength

Withstands 3000V AC
minimum
3-Phase

Phase

Dimensions

Weight	2.6 lb.
Width	6 in

General

Specifications	PBT Enclosure and handle
Style	Standard Duty
Mounting Type	External Mounting Feet
UPC	783585789088
Type	Disconnect Switches
Enclosure Type	Non-Metallic
Material	PBT

Logistics

Carton Quantity	8
-----------------	---

Operational

Operating Cycles	Minimum 6,000 cycles at rated switch load
Operating Temperature	• Maximum continuous 75 °C • Minimum continuous without impact -40 °C
Actuator	Rotary Handle

Product Assets

[Catalog Page \[English\]](#)