

Hubbell-PRO Motor Disconnects

30, 60, and 100 Ampere Unfused Disconnect Switches
“Suitable as Motor Disconnect”

About

- UL 508 / UL 60947-4-1 rated
- Suitable as a motor disconnect
- IP67 and Type 4X thermoplastic enclosure
- HP rated switch
- 30A, 60, and 100A disconnects available

Features

- Accepts up to 2 auxiliary contacts
- OSHA LO/TO handle
- Moveable mounting feet
- Stainless steel captive screws
- Cover cannot be removed with switch in “on position”
- Available accessories include include auxiliary contact(s), neutral block and conduit hub



Catalog Number	Description
HPD30	HUBBELL-PRO DISC, 30A, IP67
HPD60	HUBBELL-PRO DISC, 60A, IP67
HPD100	HUBBELL-PRO DISC, 100A, IP67
HPDRF1	HUBBELL-PRO DISC,30A REPLC Mounting Feet
HPDRF2	HUBBELL-PRO DISC,60/1000A Replacement Feet
HPD30RC	HUBBELL-PRO DISC, 30A Replacement Cover
HPD60RC	HUBBELL-PRO DISC, 60A Replacement Cover
HPD100RC	HUBBELL-PRO DISC, 100A Replacement Cover
HPDAC2	NO & NC AUX Contact, Break Before Break