

Straight Blade Devices, Receptacles,
Duplex, Commercial Grade, Corrosion
Resistant, Smooth Face, 15A 125V, 2-Pole 3-
Wire Grounding, 5-15R, Side Wired.

By Hubbell Wiring Device-Kellems
Catalog # [IG15CRI](#)

Straight Blade Duplex Receptacle Corrosion Resistant, Smooth
Face 15A

Features

- Triangle marking on face indicates isolated ground
- Smooth face
- Triple wipe contacts

Application

Commercial Specification Grade

Performance

Electrical - Current Interrupting - Certified for current
interrupting at full rated current, Electrical - Dielectric Voltage -
Withstands 2,000V minimum, Environmental - Flammability - UL
94 V-2, Environmental - Operating Temperatures - Maximum
continuous 75°C minimum -40°C (w/o impact), Mechanical -
Product Identification - Ratings are a permanent part of the
device, Mechanical - Terminal Accommodation - #14-#10 AWG
copper stranded or solid conductor only, Mechanical - Terminal
Identification - Terminals identified in accordance with UL 498
and CSA

Specifications

Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	Yes
Nema Rating	5-15R
Industry Standard(s)	• Certified to CSA C22.2, No. 42 • Fed. Spec. W-C-596 • NEMA® WD-6 Compliant • UL Listed to UL498 File No. E2186

Conductor

Number Of Wires	3-Wire
Wire Size	#14 AWG to #10 AWG
Number Of Poles	2-Pole

Current

Amperage Rating	15 A
Voltage Rating Description	125 V
Dielectric Strength	Withstands 2,000V minimum
Current Rating	15 A



Voltage Rating	125 V
Wattage	1875 W
Connectivity	Side Wired Screw Terminals
Phase	Single Phase
Current / Amperage Rating	15 A

Dimensions

Length	1.32 in
Display Size	Standard Sized Product
Weight	0.15 lb.
Height	3.28 in
Width	0.83 in
Dimensions	1.32 in x 0.83 in x 3.28 in

General

Color	Ivory
Style	Smooth Face
Series	Commercial Specification Grade

Specifications	• Automatic Self-grounding Staple - Stainless steel • Base - Nylon • Face - Nylon • Ground Contacts - Brass • Mounting Screws - Galvanized Steel • Mounting Strap - .040 in. (1) Galvanized steel • Power Contacts - .030 in. (.8) Brass • Terminal Screws - Plated steel • Wire Clamp - .062 in. (1.6) Nickel plated steel
UPC	783585147581
Type	Standard Duplex
Material - Mounting Hardware	Screw Mounting
Item Type	Traditional Duplex
Material	Nylon

Logistics

Carton Quantity	10
-----------------	----

Operational

Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
Horsepower - Maximum	0.5

Product Assets

- [Catalog \[English\]](#)
- [Catalog Page \[English\]](#)
- [Catalog Page \[English\]](#)
- [Installation Manual \[Spanish, French, English\]](#)



A Hubbell brand