

Kellems Wire Management, Cord
Connectors, 90 Degree Male 1.25-1.38", 1
1/4", Aluminum

By Hubbell Wiring Device-Kellems
Catalog # [NHC1054](#)

Kellems Wire Management, Cord Connectors, 90 Degree Male
1.25-1.38", 1 1/4", Aluminum

Features

- Cast aluminum cord connector, one-piece design with machined threads
- Lock nuts sold separately
- UL514B Tray cable rated for dry locations

Application

90 Degree Male- Form 5

Performance

Environmental - Hazardous Locations - Used in hazardous locations per Class I Div. 2, Class II Div. 1 & 2, Class III Div. 1 & 2 in accordance with the NEC., Environmental - Operating Temperatures - -30°F to +225°F (-34°C to +107°C)

Specifications

Environmental Conditions	Suitable For Use In Wet Locations When Used With A Listed Nylon Washer Between Box And Fitting.
EU RoHS Indicator	Yes
Nema Rating	NEMA Type 4, 4X, 12 and 13
Industry Standard(s)	UL Listed

Conductor

Number Of Conductors	Single
Conductor Range	1.25-1.38 in (31.7- 34.9 mm)



Dimensions

Hub Size	1-1/4"
Display Size	1 1/4" NPT

General

Series	Standard Duty Series
Specifications	• Cord Diameter Inches (mm) - 1.25"-1.38" (31.7-34.9) • Form Size - F5 • Material - Aluminum • NPT Hub Size - 1 1/4 Inch
UPC	783585201542
Type	90° Male
Material - Mounting Hardware	Locknut or Tapped Opening
Item Type	Cord Connectors
Material	Aluminum, Cast

Logistics

Carton Quantity	10
-----------------	----

Operational

Temperature Rating	Minimum -30 Deg F to 225 Deg F (-34 Deg C to 107 Deg C)
--------------------	---

Product Assets

- [Catalog \[English\]](#)
- [Catalog Page \[English\]](#)
- [Installation Manual \[English\]](#)