

Kellems Wire Management, Liquidtight System, PolyTuff® Non-Metallic Liquidtight Fittings, 90 Degree Male Liquid-Tight Connector, 1/2", Black

By Hubbell Wiring Device-Kellems
Catalog # [P0509NBK](#)

Kellems Wire Management, Liquidtight System, PolyTuff® Non-Metallic Liquidtight Fittings, 90 Degree Male Liquid-Tight Connector, 1/2", Black

Features

- Nylon compression nut has a tapered dome to tighten ferrule onto conduit
- Neoprene O-ring provides liquidtight seal
- Non integral ferrule provides conduit seal and pullout protection

Application

Fittings are to be used with PolyTuff® I and PolyTuff® II

Performance

Environmental - Flammability - UL 94X-2, Environmental - Operating Temperature - -30°F to +225°F (-34°C to +107°C)

Specifications

Standards - RoHS Compliance Status	CM
Industry Standard(s)	• CSA Certified • UL Listed:UL50 Type 4X, 12 and 13

Dimensions

Trade Size	1/2
Dimension - L Length Overall mm	2.91 in



Weight	0.05 lb.
Height	1.98 in
Dimension - Thread Size	1/2" NPT

General

Color	Black
Style	90°
Product Type Specifications	PolyTuff® Fittings • Fitting - Nylon • Lockwasher - Zinc plated steel • Sealing Ring - Elastomer
UPC	783585810003
Type	PolyTuff® Non-Metallic Liquidtight Fittings
Material	Nylon

Logistics

Pallet Quantity	5400
Carton Quantity	25

Product Assets

[Catalog \[English\]](#)
[Catalog Page \[English\]](#)