HUBBELL
Wiring Device-Kellems

Kellems Wire Management, Liquidtight System, SwivelLok® Multi-Position Male, Liquid Tight Connector, 1/2", Non-Metallic, Black



By Hubbell Wiring Device-Kellems
Catalog # PS0509NBK

Kellems Wire Management, Liquidtight System, SwivelLok® Multi-Position Male, Liquid Tight Connector, 1/2", Non-Metallic, Black

Features

- Nylon compression nut has a tapered dome to tighten ferrule onto conduit
- Neoprene O-ring provides liquidtight seal
- Non integral ferrule provides conduit seal and pullout protection
- Swiveled to any position from straight to 90°

Application

Fittings are to be used with PolyTuff® I and PolyTuff® II

Performance

Environmental - Flammability - UL 94X-2, Environmental - Operating Temperature - –30°F to +225°F (–34°C to +107°C)

Specifications

Standards - RoHS Compliance Status	CM
Industry Standard(s)	• CSA Certified • UL Listed:UL50 Type 4X, 12 and 13

Dimensions

Trade Size	1/2
Weight	0.074 lb.

General

Color	Black
Style	SwivelLok® Multi-Position
Product Type	PolyTuff® SwivelLok® Fittings
Specifications	• Material - Nylon • Sealing Ring - Neoprene
UPC	783585339108
Type	PolyTuff® SwivelLok® Non-Metallic Liquidtight Fittings
Material	Nylon

Logistics

Pallet Quantity	6400
Carton Quantity	25

Product Assets

Catalog [English]
Catalog Page [English]
Installation Manual [English]

© 2026 Hubbell Incorporated. All rights reserved