

Kellems Wire Management, Liquidtight System, SwivelLok® Multi-Position Male Liquid Tight Connector, 3/4", Non-Metallic, Black

By Hubbell Wiring Device-Kellems
Catalog # [PS0759NBK](#)

Kellems Wire Management, Liquidtight System, SwivelLok® Multi-Position Male Liquid Tight Connector, 3/4", Non-Metallic, Black

Features

- Nylon compression nut has a tapered dome to tighten ferrule onto conduit
- Neoprene O-ring provides liquidtight seal
- Non integral ferrule provides conduit seal and pullout protection
- Swiveled to any position from straight to 90°

Application

Fittings are to be used with PolyTuff® I and PolyTuff® II

Performance

Environmental - Flammability - UL 94X-2, Environmental - Operating Temperature - -30°F to +225°F (-34°C to +107°C)

Specifications

Standards - RoHS Compliance	CM
Status	
Industry Standard(s)	• CSA Certified • UL Listed:UL50 Type 4X, 12 and 13

Dimensions



Trade Size	3/4
Weight	0.1 lb.
General	
Color	Black
Style	SwivelLok® Multi-Position
Product Type	PolyTuff® SwivelLok® Fittings
Specifications	• Material - Nylon • Sealing Ring - Neoprene
UPC	783585339146
Type	PolyTuff® SwivelLok® Non-Metallic Liquidtight Fittings
Material	Nylon
Logistics	
Pallet Quantity	3360
Carton Quantity	10
Product Assets	
Catalog [English]	
Catalog Page [English]	
Installation Manual [English]	