

Non-Metallic Raceway, Non-Latching
PremiseTrak, PREM-TRAK1, Base, Cover, 7'
Length

By Hubbell Wiring Device-Kellems
Catalog # [PT1BC7](#)

Non-Metallic Raceway, Non-Latching PremiseTrak, PREM-TRAK1,
Base, Cover, 7' Length

Features

- Office white color
- UL Listed and CSA Certified to 600 volts
- Single and two channel latching raceways are dual-rated for both power and data applications

Application

7' Base and Cover

Performance

Environmental - Flammability - UL94V-0, Environmental -
Operating Temperature - -25.6° to 158° F

Specifications

Standards - RoHS Compliance Status	CM
Non Hazardous Location	Non Hazardous
EU RoHS Indicator	Yes
Industry Standard(s)	• CSA Standard C22.2 no. 62 • E118895 / E119190 • UL Standard UL 5A

Configuration

Knockouts	None
-----------	------

Dimensions



Length	7 ft
Width	0.75 in

General

Color	Office White
Style	Single Channel
Enclosure Type	NEMA 1 Rating
Series	PT1
Specifications	• Channel Area - 0.29 (sq. in.) • Crush Resistance - 300 lbs • Impact Resistance - 5 ft. lbs. • Material - UV Stabilized PVC
UPC	783585335827
Type	Base and Cover
Construction	Extruded Plastic
Item Type	PT1, PremiseTrak 1- Non Latching
Material	Thermoplastic
Cover Type	Integral

Logistics

Carton Quantity	70
-----------------	----

Product Assets

- [Catalog \[English\]](#)
[Catalog Page \[English\]](#)
[Installation Manual \[English\]](#)