HUBBELL
Wiring Device-Kellems

Heavy Duty Products, IEC Pin and Sleeve Devices, Industrial Grade, Accessories, Liquid Tight Adapter



By Hubbell Wiring Device-Kellems
Catalog # SAA34

Heavy Duty Products, IEC Pin and Sleeve Devices, Industrial Grade, Accessories, Liquid Tight Adapter, For 16 and 20A 3 and 4-Wire, 3/4" NPT, Furnished with Hardware, Machined Aluminum

Features

- Industrial Grade
- Accessories
- Liquid Tight Adapter

Application

16 and 20 Amp, 3 and 4 Wire

Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - Withstands 3,000V AC, Electrical - Max Working Voltage - 600V AC RMS, Environmental - Flammability - UL94-5VA and V-0 classification, Environmental - Ingress Protection - IP67 Suitability, Environmental - Operating Temperatures - Maximum Continuous: 75° C, Minimum Continuous: -40° C w/o impact, Mechanical - Impact Resistance - In accordance with UL746C, Mechanical - Product Identification - Identification and ratings are a part of the external label and molded into the receptacle mount, Mechanical - Terminal Identification - Terminals identified in accordance with North American and International conventions

Specifications

Environmental Conditions	Watertight
EU RoHS Indicator	No
Nema Rating	Non-NEMA
Industry Standard(s)	UL Listed

Configuration

Cord Type	All Portable

Current

Connectivity	Pressure Terminal Screws

Dimensions

Display Size	Standard Sized

General

Color	Aluminum
Style	3/4" NPT
Series	Accessories
Specifications	• Accessory Item - Conduit Adapter • Assembly Screws - Stainless Steel • Gaskets - Neoprene • Hinge Spring - Stainless Steel
UPC	783585887159
Type	Liquidtight Adapter
Material - Mounting Hardware	Cord Mounted
Item Type	Liquid-Tight Adapter
Material	Aluminum

Logistics

Carton Quantity	5

Product Assets

Catalog [English]
Catalog Page [English]
Installation Manual [English]

© 2026 Hubbell Incorporated. All rights reserved