HUBBELL
Wiring Device-Kellems

Kellems Wire Management, Cord Connectors, European Style, .45-.71", 3/4", Black



By Hubbell Wiring Device-Kellems
Catalog # SEC75BA

Kellems Wire Management, Cord Connectors, European Style, .45-.71", 3/4", Black

Features

- Low profile
- Connector body is a one-piece design with machined threads

Application

Straight Male Connector

Performance

Environmental - Flammability - UL 94V-2, Environmental - Operating Temperatures - -22°F to 225°F (-30°C to 107°C), Environmental - Protection Class - IP66 Suitability

Specifications

Standards - RoHS Compliance Status	CM
Environmental Conditions	Suitable For Use In Wet Locations When Used With A Listed Nylon Washer Between Box And Fitting.
EU RoHS Indicator	Yes
Nema Rating	IP66
Industry Standard(s)	UL Listed

Conductor

Number Of Conductors	Single
Conductor Range	0.45-0.71 in (11.4-18.0 mm)

Dimensions

Hub Size	3/4"
Display Size	3/4" NPT

General

Color	Black
Series	Low Profile NPT
Specifications	• Body - Nylon • Cord Diameter Inches (mm) - .45"-.71" (11.4-18.0) • Gland - Buna N • NPT HUB Size - 3/4 Inch
UPC	783585018164
Type	Connector
Material - Mounting Hardware	Locknut or Tapped Opening
Item Type	Low Profile Cord Connectors
Material	Non-Metallic

Logistics

Pallet Quantity	10800
Carton Quantity	50

Operational

Temperature Rating	Minimum -22 Deg F to 225 Deg F (-30 Deg C to 107 Deg C)

Product Assets

Catalog [English]
Catalog Page [English]

© 2026 Hubbell Incorporated. All rights reserved