HUBBELL
Wiring Device-Kellems

Kellems Wire Management, Cord Connectors, Straight Male, .19-.25", 3/8", Aluminum



By Hubbell Wiring Device-Kellems
Catalog # SHC1009

Kellems Wire Management, Cord Connectors, Straight Male, .19-.25", 3/8", Aluminum

Features

- Aluminum cord connector provides durable performance
- Knurled finish makes them easy to handle and maintain UL listing by hand tightening
- Lightweight design

Application

Straight Male- Form 1

Performance

Environmental - Hazardous Locations - Used in hazardous locations per Class I Div. 2, Class II Div. 1 & 2, Class III Div. 1 & 2 in accordance with the NEC, Environmental - Operating Temperatures - -30°F to +225°F (-34°C to +107°C)

Specifications

Standards - RoHS Compliance Status	CM
Environmental Conditions	Suitable For Use In Wet Locations When Used With A Listed Nylon Washer Between Box And Fitting.
EU RoHS Indicator	Yes
Nema Rating	NEMA Type 4, 4X, 12 and 13
Industry Standard(s)	UL Listed

Conductor

Number Of Conductors	Single
Conductor Range	0.19-0.25 in (4.7- 6.3 mm)

Dimensions

Hub Size	3/8"
Display Size	3/8" NPT

General

Color Code	Red
Series	Standard Duty Series
Specifications	• Cord Diameter Range Inches (mm) - .19"-.25" (4.7-6.3) • Form Size - F1 • Material - Aluminum • NPT Hub Size - 3/8 Inch
UPC	783585200095
Type	Straight Male
Material - Mounting Hardware	Locknut or Tapped Opening
Item Type	Cord Connectors
Material	Aluminum

Logistics

Pallet Quantity	22000
Carton Quantity	50

Operational

Temperature Rating	Minimum -30 Deg F to 225 Deg F (-34 Deg C to 107 Deg C)

Product Assets

Catalog [English]
Catalog Page [English]
Installation Manual [English]

© 2026 Hubbell Incorporated. All rights reserved