Straight Male Cord Connectors

Form Size 5-8

UL Listed to Type 4, 4X, 12 and 13

IP66* SUITABILITY





Straight Male

NPT Hub Size	Cord Diameter Inches (mm)		Form Size	Cast Aluminum	Malleable Iron
1	.88"-1.00" 1.00"-1.13" 1.13"-1.25" 1.25"-1.38"	(22.2-25.4) (25.4-28.6) (28.6-31.7) (31.7-34.9)	F5	**SHC1046** **SHC1047**** **SHC1048**** **SHC1049****	— — — —
1-1/4	.75"-.88" .88"-1.00" 1.00"-1.13" 1.13"-1.25" 1.25"-1.38"	(19.0-22.2) (22.2-25.4) (25.4-28.6) (28.6-31.7) (31.7-34.9)	F5	**SHC1050** **SHC1051** **SHC1052** **SHC1053** **SHC1054****	— — **SHC1052ZP** **SHC1053ZP** **SHC1054ZP**
1-1/2	.75"-.88" .88"-1.00" 1.00"-1.13" 1.13"-1.25" 1.25"-1.38"	(19.0-22.2) (22.2-25.4) (25.4-28.6) (28.6-31.7) (31.7-34.9)	F5	**SHC1055** **SHC1056** **SHC1057** **SHC1058** **SHC1059**	— — **SHC1057ZP** **SHC1058ZP** **SHC1059ZP**
1-1/2	1.38"-1.50" 1.50"-1.63" 1.63"-1.75" 1.75"-1.88"	(34.9-38.1) (38.1-41.3) (41.3-44.4) (44.4-47.6)	F6	**SHC1061** **SHC1062**** **SHC1063**** **SHC1064****	— — — —
2	1.25"-1.38" 1.38"-1.50" 1.50"-1.63" 1.63"-1.75" 1.75"-1.88"	(31.7-34.9) (34.9-38.1) (38.1-41.3) (41.3-44.4) (44.4-47.6)	F6	**SHC1065** **SHC1066** **SHC1067** **SHC1068** **SHC1069**	— — — — —
2	1.69"-1.81" 1.81"-1.94" 1.94"-2.06" 2.06"-2.19" 2.19"-2.31"	(42.9-46.0) (46.0-49.2) (49.2-52.4) (52.4-55.6) (55.6-58.7)	F7	**SHC1070** **SHC1071** **SHC1072**** **SHC1073**** **SHC1074****	— — — — —
2-1/2	1.69"-1.81" 1.81"-1.94" 1.94"-2.06" 2.06"-2.19" 2.19"-2.31" 2.31"-2.44"	(42.9-46.0) (46.0-49.2) (49.2-52.4) (52.4-55.6) (55.6-58.7) (58.7-61.9)	F7	**SHC1076** **SHC1077** **SHC1078** **SHC1079** **SHC1080** **SHC1081****	— — — — — —
3	1.69"-1.81" 1.94"-2.06" 2.06"-2.19" 2.19"-2.31" 2.31"-2.44"	(42.9-46.0) (49.2-52.4) (52.4-55.6) (55.6-58.7) (58.7-61.9)	F7	**SHC1086** **SHC1088** **SHC1089** **SHC1090** **SHC1091**	— — — — —
3	2.44"-2.63" 2.63"-2.81" 2.81"-3.00" 3.00"-3.25"	(61.9-66.7) (66.7-71.4) (71.4-76.2) (76.2-82.5)	F8	**SHC1092** **SHC1093** **SHC1094** **SHC1095****	— — — —

Note: See pages Y-77 to Y-87 for technical information and dimensional drawings.
**IP66 Suitability when used with optional metal clad O-ring, see page Y-74 for additional information.*
***Cable jacket may have to be stripped to pass through connector body.*
Locknuts sold separately. See page Y-74 for additional information.

Dimensions in Inches (mm)