

Switches and Lighting Controls,
Industrial/Commercial Grade,
SNAPConnect® Series, Toggle Switches,
Single Pole, 15A 120/277V AC Toggle, North
American

By Hubbell Wiring Device-Kellems
Catalog # [SNAP1201LANA](#)

Switches and Lighting Controls, Industrial/Commercial Grade,
SNAPConnect® Series, Toggle Switches, Single Pole, 15A
120/277V AC, Light Almond Toggle, North American

Features

- Steel, zinc plated bridge is corrosion resistant
- Thread cleaning captive mounting screw
- Automatic self-grounding staple assures continuity to wall box

Application

General Purpose

Performance

Electrical - Dielectric Voltage - Withstands 1500V AC minimum for 1 minute, Electrical - Max. Continuous Current - 15A, Electrical - Max. Working Voltage - 277V AC, Electrical - Overload - Minimum 4.8 times rated current for 100 cycles, Electrical - Temperature Rise - 30°C maximum at rated current, Environmental - Flammability - UL 94V-2, Environmental - Operating Temperature - Max. continuous: 75°C, Min. continuous: -40°C without impact, Mechanical - Terminal Accommodations - Uses SNAPConnect® Connector

Specifications

EU RoHS Indicator	No
Industry Standard(s)	UL Listed

Conductor

Number Of Poles	Single Pole
-----------------	-------------

Current

Amperage Rating	15 A
Voltage Rating Description	120-277 VAC
Dielectric Strength	Withstands 1500V AC minimum for 1 minute
Current Rating	15 A
Voltage Rating	120-277 VAC
Temperature Rise - Max.	30°C maximum at rated current



Current / Amperage Rating	15 A
---------------------------	------

Dimensions

Length	4.18 in
Height	1.74 in
Width	1.3 in
Dimensions	4.18 in x 1.3 in x 1.74 in

General

Color	Light Almond
Style	Single Pole
Series	SNAPConnect® Series
Specifications	• Base Material - Thermoplastic, Black • Contacts - Silver Alloy • Terminals - Brass • Toggle Material - Thermoplastic • Top Material - Thermoplastic, Blue
UPC	783585186498
Type	Toggle
Item Type	Single Pole Toggle Switch
Material	Thermoplastic

Logistics

Carton Quantity	10
-----------------	----

Operational

Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
-----------------------	--

Product Assets

[Catalog \[English\]](#)
[Catalog Page \[English\]](#)
[Installation Manual \[Spanish, French, English\]](#)