HUBBELL
Wiring Device-Kellems

Temporary Power Products, Spider II Portable Power, Cable Sets and Receptacles, Wall Receptacle, 50A 125/250V



By Hubbell Wiring Device-Kellems
Catalog # SR50

Temporary Power Products, Spider II Portable Power, Cable Sets and Receptacles, Wall Receptacle, 50A 125/250V

Features

- Spider II Portable Power
- Cable Sets and Receptacles
- Wall Receptacle
- 50A 125/250V

Application

Temporary Power Distribution

Specifications

Industry Standard(s)	UL 1640 cUL and CSA, UL 943
Environmental Conditions	Indoor/Outdoor
EU RoHS Indicator	No

Conductor

Number Of Poles	2-Pole

Current

Amperage Rating	50 A
Connectivity	Plug Together
Phase	Single Phase
Current / Amperage Rating	50 A
Current Rating	50 A

Dimensions

Display Size	Standard Sized Product

General

Specifications	• Code Compliance - NEC®, ANSI/NFPA 70 • Enclosure Type - 3R, rainproof, suitable for use in damp locations • Environment - Moisture Resistance
Style	Pre-Wired Wall Mounted Receptacle
UPC	783585830506
Type	Device
Item Type	Wall Mounted Single
Material	Thermoplastic

Product Assets

Catalog [English]
Catalog Page [English]

© 2026 Hubbell Incorporated. All rights reserved