

EdgeConnect™ Series, Straight Blade Duplex Receptacle, 20A, No ears, Black

By Hubbell Wiring Device-Kellems
Catalog # [BR20STBKM1](#)

Short Strap, BR20STBK EdgeConnect™, Black



Features

- Back wired screwless termination for faster termination time
- No need for screwdriver and torque wrench
- Spring Termination eliminates strand relaxation
- Simple color coded plungers for easy and quick wiring
- Use small screwdriver to lift plunger and rewire as needed

Application

Spring clamp terminal strengthens over time providing a more reliable connection.

Specifications

Industry Standard(s)	UL Listed to UL498 File No. E2186, c-UL-us No. 42 File 285, Fed. Spec. W-C-596, NEMA® WD-6 Compliant
Certification - CSA Approved	Terminals Identified in Accordance with UL 498 and CSA
Nema Rating	5-20R
Conductor	
Number Of Wires	3-Wire
Number Of Poles	2-Pole
Current	
Current / Amperage Rating	20 A
Dielectric Type	Withstands 2,000V minimum
Current Interrupting	Certified for current interrupting at full rated current

Voltage Rating 125 V

Dimensions

Size 3.28x1.58x1.38

General

Item Type	Receptacle
Type	Short strap, no ears
Series	EdgeConnect™ Series
U_Flammability	UL 94 V-2
Material	Thermoplastic/C
Terminal Type	#14 - #10AWG Wire (Solid or Stranded) Copper or UL listed CCA conductors only
UPC	783585799865
Style	Flat Face
Application - For Use On	Ratings are a permanent part of the device
Color	White

Logistics

Carton Quantity 10

Operational

Temperature Range Maximum continuous 75°C, minimum -40°C without impact

Product Assets

[Installation Manual \[Spanish, French, English\]](#)