

Hubbell-PRO 30, 60 and 100A Motor Disconnects

Features and Benefits

Hubbell-PRO motor disconnects are value engineered for commercial and light duty applications. They are available in 30A and 60A versions with optional early break auxiliary contacts for use with VFDs and other auxiliary equipment.

Key Features:

- UL 508 / UL 60947-4-1
- HP Rated
- IP67
- Accepts up to 2 auxiliary contacts
- OSHA Compliant lockout/tagout handle
- Compact, installation friendly enclosure



Ordering Information

Catalog Number	Amps	Ingress Protection	NO&NCAux Contacts	NO Aux Contacts**	Ground	Neutral*	Conduit Hub*
HPD30	30A	IP67	HBLAC1	HBLAC2	HBL30RGB	HBL30RNB*	HUB75*
HPD60	60A	IP67	HBLAC1	HBLAC2	HBL60RNB	HBL30RNB*	HUB125A*
HPD100	100A	IP67	HBLAC1	HBLAC2	HBL100RNB	HBL30RNB*	HUB125A*

Note: *Not included with enclosure.

**Break before main break and not included with enclosure.

30 Amp Accessories

Amperage	Replacement Feet	Replacement Cover
30A	HPDRF1	HPDS30RC
60A	HPDRF2	HPD60RC
100A	HPDRF2	HPD100RC

Dimensions in Inches (mm)