

Product availability : Stock - Normally stocked in distribution facility



Price\* : 170.00 USD



### Main

Device short name	C
Enclosure type	Standard
Head type	Turret head rotary lever type C
Provided equipment	Receptacle
Series name	Heavy duty

### Complementary

Line Rated Current	10 A
Body material	Zinc alloy
Cable entry	NPT conduit entry 0.5 in
Contact code designation	Q600 A600
Contact form	Form Z SPDT-DB
Contacts material	Silver alloy (Ag/Ni)
Contact operation	Snap action
Contacts type and composition	1 NO/1 NC
Maximum displacement angle	90 °
Permissible voltage	<= 600 V
Pilot light	Without pilot lamp
Specificity of operator	Standard pre-travel
Switch actuation	CCW
Tilting angle	10 °
Torque value	4 lbf.in
Tripping angle	4 °
Type of operator	Spring return lever arm to be ordered separately

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Environment

Ambient air temperature for operation	-20...185 °F
Product certifications	CE UL listed CSA

## Ordering and shipping details

Category	21499 - 9007 C LIMIT SWITCHES
Discount Schedule	DS1
GTIN	00785901538219
Nbr. of units in pkg.	1
Package weight(Lbs)	1.25
Returnability	N
Country of origin	MX

## Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Will not be compliant Will not be compliant
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

## Contractual warranty

Warranty period	18 months
-----------------	-----------