









A-51® Incandescent Factory Sealed Luminaire Accessories

For Group C and D Locations. Explosionproof

Suitable for use in Wet Locations. UNILETS for use with Threaded Metal Conduit.

Class I, Division 1 and 2, Groups C, D
Class II, Division 1 and 2, Groups E, F, G
Class III

| Mounting Hoods | | |
|---|------------------------|----------------|
| Type | Hub Size (Inches) | Catalog Number |
| Pendant — One Hub, Rigid or Flexible Mounting | | |
|  | 1/2 | AAP-50 |
| | 3/4 | AAP-75 |
| | 1 | AAP-100 |
| Ceiling — Four Hubs, Three Close-up Plugs | | |
|  | 1/2 | AAC-50 |
| | 3/4 | AAC-75 |
| | 1 | AAC-100 |
| 25° Stanchion — Not UL Listed — One Hub | | |
|  | 1-1/2 | AAN-150 ① |
| Long Bracket — Four Hubs, Three Close-up Plugs | | |
|  | 1/2 | AALB-50 |
| | 3/4 | AALB-75 |
| | 1 | AALB-100 |
| 15° Short Bracket — Two Hubs, One Close-up Plug | | |
|  | 1/2 | AASB-50 |
| | 3/4 | AASB-75 |
| Type | Catalog Number | |
| Fixture Units | | |
|  | 60-100 W A-21 | AAU-1N |
| | 150-300 W A-23 & PS-25 | AAU-15N |
| | 200-300 W PS-30 | AAU-2NS |
| Prismatic Glass Globes | | |
|  | 60-100 W (AAU-1N) | AAGL-1PR |
| | 150-300 W (AAU-15N) | AAGL-1PR |
| | 200-300 W (AAU-2NS) | AAGL-2PR |
| Aluminum Guards | | |
|  | 60-100 W (AAU-1N) | AAGU-1 |
| | 150-300 W (AAU-15N) | AAGU-1 |
| | 200-300 W (AAU-2NS) | AAGU-2 |

① 1-1/2" tapped hub furnished with a 1-1/2" to 1-1/4" reducer.




A-51® Incandescent Factory Sealed Luminaires

For Group A and B Locations. Explosionproof

Suitable for use in Wet Locations. UNILETS for use with Threaded Metal Conduit.

Class I, Division 1 and 2, Groups A, B, C, D
 Class II, Division 1 and 2, Groups E, F, G
 Class III

Mounting Hoods

| | Type | Hub Size (Inches) | Catalog Number |
|--------------------------|---|--|--|
| Pendant |  | One Hub, Rigid or Flexible Mounting | 1/2 AAP-50 ① 3/4 AAP-75 ① |
| | | | |
| Ceiling |  | Four Hubs, Three Close-up Plugs | 1/2 AAC-50 3/4 AAC-75 |
| | | | |
| 15° Short Bracket |  | Two Hubs, One Close-up Plug | 1/2 AASB-50 3/4 AASB-75 |
| | | | |

| | Description | Catalog Number |
|--------------------------------|--|-----------------|
| Fixture Units | 60-200 W | AAUA-15 |
| | PS-25 | |
| | 200-300 W | AAUA-2 |
| | PS-30 | |
| Globe and Ring Assembly | 60-200 W (AAUA-15) | AAGLA-15 |
| | 200-300 W (AAUA-2) | AAGLA-2 |
| Aluminum Guards | 60-200 W (AAUA-15) | AAGUA-15 |
| | 200-300 W (AAUA-2) | AAGU-2 |
| Medium Base Lamp Socket | 60-200 W (AAUA-15) | AASPA-15 |
| | 200-300 W (AAUA-2) | AASPA-22 |
| Connection Block | Fits all A-51 and AA-51 mounting hoods 60-300 W | VPT-7 |

① Group A pendant mount only.

LIGHTING: EXPLOSIONPROOF – AREA – INCANDESCENT

Lighting