

Open Switches T&B Catalog Number:

OT100FT3 80432544047

Status: Active

Description:

UPC Number:

3 pole, 100 amps rated at 600 VAC, UL 98, door mounted open non-fusible disconnect switch

Tusible discorniect switch	
Features	
	Quick make, quick brake mechanism
	Extremely compact size
	Finger-proof construction with no hazardous ex-
	posed parts
Application	
	Suitable for use as motor disconnects or industri-
	al control panel disconnects on service entrance
	equipment, panelboards, switchboards, industrial
	control equipment, motor control centers, etc.
	Motor feeder applications and motor feeder short
	circuit and ground fault protection
General	
Style	Door Mounted
Number of Poles	3
Series	Non-fusible
Approvals	
UL Class	UL 98
Dimension Information	
H x W x D (inches)	3.94 x 2.76 x 2.93
Specifications	
Rated Current (Amps)	100
Rated Voltage AC	600
Packaging	
T&B Inner Pack	1
Package in Units	10
T&B Sold in UOM	Each
T&B Weight Per UOM	0.96 lbs. Each

For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com