



SNA Terminal Blocks

T&B Catalog Number:

1SNA400305R1000

UPC Number:

80432551313

Status:

Active

Description:

Gray, feed through terminal block with 22 mm spacing, 159 Amp rated UL current with screw clamp connection that accepts 2 - 0000 AWG UL wire range

Features

Self-locking clamp design prevents screw loosening

Funneled side entry for up to two ferruled or non-ferruled solid or stranded wires

Touch-safe IP20 protection

High quality steel offers a very high over-torque resistance

Compensates for the flattening of copper under contact pressure

Clamp is protected from harsh environments by a zinc bichromate surface treatment

Application

For use with applications ranging from standard distribution and control panels, to specialized applications in key industries such as traction, energy, maritime, explosive atmospheres, material handling, etc.

General

T&B Replacement Catalog Number	040030510
Style	Feed Through
Color	Gray
Mounting	DIN 1-3
Series	D 70/22
Connection Technology	Screw Clamp
UL Wire Range (AWG)	2-0000
Rated IEC Wire Range (Solid) (mm ²)	70

Dimension Information

L x W x H (mm)	84 x 22 x 74.5
Spacing (mm)	22
L x W x H (in)	3.3 x 0.868 x 2.92
Spacing (inches)	0.866

Specifications

UL Current (Amps)	159
UL Voltage (VAC)	600
IEC Voltage (VAC)	1000
IEC Current (Amps)	192
CSA Voltage (VAC)	600
CSA Current (Amps)	159

Packaging

T&B Order Multiple	10
T&B Inner Pack	10
Package in Units	60
T&B Sold in UOM	Each

T&B Weight Per UOM	0.47 lbs. Each
--------------------	----------------

Certifications

Approvals	UL, IEC, CSA
-----------	--------------

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com