



Surge Protection Devices T&B Catalog Number:

UPC Number:

OVRT240150PU

Status:

80432556441

Description:

Active

Single pole OVR DIN rail surge protection device with a surge capacity of 40 kA and maximum voltage of 320V

Features

Fast acting metal oxide varistor (MOV) technology limits overvoltage to values compatible with the sensitive equipment connected to the network

Each cartridge is equipped with a mechanical end of life indicator

Pluggable cartridges allow replacement of dead cartridges without isolating the electrical circuit

Application

For protecting valuable equipment against transient surges and to help keep operations up and running

Installation at branch panels, control panels and terminal equipment is recommended to provide the most complete protection.

General

Mounting Method Din rail

Number of Poles 1

Terminal Type Screw

Approvals

UL Class UL1449 3rd edition, type 4 recognized component

Dimension Information

H x W x D (inches) 3.3 x 2.6 x .7

H x W x D (mm) 85 x 64.8 x 17.8

Specifications

Current Less Than 0.1 mA

Maximum Continuous Operating Voltage (V) 175

Service Voltage-Single Phase 120V

Service Voltage-Split Phase 240/120V

Service Voltage-Wye 208Y/120V

Surge Capacity (kA) 40

Voltage Protection Rating (kV) 0.6

Frequency Rating (Hz) 50 - 60

Packaging

Package in Units 1

T&B Sold in UOM Each

T&B Weight Per UOM 0.32 lbs. Each

Application Support

Product Brochure Available on Website

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com