

SNA Terminal Blocks T&B Catalog Number:

012511813

UPC Number: 66201995892 **Status:** Active

Status: Description:

Blue, feed through terminal block with 8 mm spacing, 50 Amp rated UL current with screw clamp connection that accepts 22-8 AWG UL wire range

range	
Features	
	Self-locking clamp design prevents screw loosening
	Funneled side entry for up to two ferruled or non- ferruled solid or stranded wires
	Touch-safe IP20 protection
	High quality steel offers a very high over-torque resistance
	Compensates for the flattening of copper under contact pressure
	Clamp is protected from harsh environments by a zinc bichromate surface treatment
Application	
	For use with applications ranging from standard distribution and control panels, to specialized applications in key industries such as traction, energy, maritime, explosive atmospheres, material handling, etc.
General	
Style	Feed Through
Color	Blue
Mounting	DIN 1-3
Series	M 6/8
Connection Technology	Screw Clamp
UL Wire Range (AWG)	22-8
Rated IEC Wire Range (Solid) (mm2)	6
Rated CSA Wire Size (AWG)	8
Dimension Information	
L x W x H (mm)	44.5 x 8 x 53
Spacing (mm)	8
L x W x H (in)	1.75 x 0.315 x 2.09
Spacing (inches)	0.315
Specifications	
LII. Ourmant (America)	50
UL Current (Amps)	50
UL Voltage (VAC)	600
Rated UL Wire Size (AWG)	8
IEC Voltage (VAC)	800
IEC Current (Amps)	41
CSA Voltage (VAC)	600
CSA Current (Amps) Packaging	55
rackaying	
T&B Order Multiple	50
T&B Inner Pack	50
Package in Units	1500



T&B Sold in UOM	Each
T&B Weight Per UOM	0.03 lbs. Each
Certifications	
Approvals	UL, IEC, CSA

For further technical assistance, please contact us...

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com