



Actual

Catalog Number: F9025
Product ID: 7TAI029790R0075
UPC Number: 78621033603
EAN Number: 05415022309423
Status: Active

Non-Insulated Ferrule, Length .472 Inches/12mm, Inner Diameter .228 Inches/5.8mm, Outer Diameter .295 Inches/7.5mm, Conductor Size 6 AWG/16mm², Copper, Tin Plated

- Ferrules ensure reliable electrical connections when terminating conductors in screw clamp terminal blocks.
- Application Tools: T3, ERG4

North American Specifications (UNSPSC)

UNSPSC	39121432 Electrical terminals
IGCC	4603 Electrical terminals
Brand Name	Sta-Kon
Type	Ferrule
Special Features	Ferrules ensure reliable electrical connections when terminating conductors in screw clamp terminal blocks.
Standard	UL E489056
Wire Size	6
Material	Copper
Color	Metallic

European Specifications (ETIM)

ETIM	EC000005 Cable end sleeve
Nominal cross section	16mm ²
Insulated	N
Material	Copper
Surface protection	Tinned
Reel packaging	N

Packaging

Inner Quantity	250
Outer Quantity	2500
Outer Dimensions (inches)	10x8x4
Weight Uom	0.63 lbs. per 1000

Documents / Support Tools

Technical Data Sheet CA	Available on Website
Technical Data Sheet Global	wsd-000319

For further technical assistance, please contact us...

Thomas & Betts - USA
 8155 T&B Blvd.
 Memphis, TN 38125
www.tnb.com

T&B Technical Support
 MS 3B-50
 8155 T&B Blvd.
 Memphis, TN 38125

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email: techsupport@tnb.com